



Multi-purpose outdoor unit for use in 4-pipe systems for the simultaneous production of chilled and hot water by means of two independent hydronic circuits. These units are able to satisfy the demand for hot and cold water simultaneously through a system that does not require seasonal switching and is therefore a valid alternative to traditional plants with chiller and boiler. Unit with two independent refrigerant circuits, each circuit works with an hermetic rotary Scroll compressors using R410A, axial fans, braze-welded plate-type exchanger and thermal expansion valve.

Control



Electronic control W3000TE

W3000TE controller feature a large format keyboard with wide LCD display in order to ensure an easy access to the machine setup and a complete view of unit's status. The assessment and intervention on the unit is managed through a multi-level menu, with selectable user's language. The led icons immediately show the operating status of various components.

As alternative, the innovative KIPLink user interface allows one to operate on the unit directly from the smartphone or tablet. The regulation operates on both water circuits featuring the step-wise regulation referred to the return water temperature with proportional logic. This allows to satisfy simultaneously the different requests of both cooling and heating, with no need of mode setting. Complete alarm management system is available, with the "black-box" and the alarm history display functions. Optional proprietary devices adjust the resources in systems made of several units. Consumption metering and performance measurement are available and supervision can be easily developed via proprietary devices or the integration in third party systems by means of the most common protocols as ModBus, Bacnet, Bacnet-over-IP, LonWorks.

Compatibility with the remote keyboard (up to 8 units). The programmable timer manages a weekly schedule organised into time bands (up to 10 daily time bands associated with different operating set points) to optimise unit performance by minimising power consumption during periods of inactivity.

Proprietary self-adaptive logic for the defrosting features the monitoring of several operational parameters. This allows to reduce the number and duration of the defrost cycles, with a benefit for the overall energy efficiency.

Refrigerant

Versions

- Basic
- SL Super-low noise version

Configurations

- Basic function

Features

UNIQUE PROPOSAL

Unit designed to satisfy the cold and the hot side requirements simultaneously, for 4-pipe systems without any particular operation mode setting

ENERGY SAVING

Energy saving guaranteed by the advanced operation's logic. The best operation mode is set completely automatically and independently by the unit's controller, in order to minimize the absorbed energy whatever the cooling and/or heating demand might be

ErP READY

The highest level of efficiency at part load can meet and exceed the minimum seasonal efficiency for heating, SCOP and for cooling, SEER, according with the eco-sustainable design requirements for all products using energy.

INTEGRATED HYDRONIC GROUP

The built-in hydronic module already contains the main water circuit components; it is available with single or twin in-line pump, for achieving both low or high head, fixed or variable speed, available for both plant and recovery circuits (up to 4 pumps).

WIDE OPERATING RANGE

The accurate condensation control (variable fan speed regulation as per standard on every model) and devoted kits allow unit's operation from -10°C to 46°C of outdoor air temperature, from -8°C to 18°C of evaporator leaving water temperature and hot water up to 55°C.

Accessories

- Touch Screen visual display
- Set-up for remote connectivity with ModBus/Echelon protocol cards
- Hydronic kit available in different configurations with 1 or 2 pumps fixed speed or variable speed, for achieving both low or high head, available for both plant and recovery circuits.
- EC fans with electronic DC brushless motor
- LOW NOISE KIT (only on no silenced versions)
- Soft starters
- Electronic expansion valve

NX-Q		0152P	0182P	0202P	0252P	0262P	0302P	0402P	0502P	0602P	
Power supply		V/ph/Hz 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50									
PERFORMANCE											
COOLING ONLY (GROSS VALUE)											
Cooling capacity	(1)	kW	43,94	50,85	58,12	64,03	71,56	85,53	110,7	137,9	168,6
Total power input	(1)	kW	12,74	14,83	17,63	19,16	22,23	25,60	33,40	42,28	56,50
EER	(1)	kW/kW	3,457	3,432	3,301	3,333	3,225	3,340	3,314	3,260	2,984
COOLING ONLY (EN14511 VALUE)											
Cooling capacity	(1)(2)	kW	43,80	50,60	57,90	63,80	71,40	85,20	110,3	137,4	168,0
EER	(1)(2)	kW/kW	3,420	3,370	3,250	3,290	3,190	3,290	3,260	3,210	2,940
ESEER	(1)(2)	kW/kW	4,170	4,110	4,020	4,150	3,970	4,050	4,030	3,970	3,680
HEATING ONLY (GROSS VALUE)											
Total heating capacity	(3)	kW	46,44	53,18	60,63	67,30	75,18	90,09	115,2	144,8	177,3
Total power input	(3)	kW	13,49	15,30	17,49	19,25	21,42	25,56	32,70	41,33	52,06
COP	(3)	kW/kW	3,437	3,477	3,463	3,487	3,514	3,520	3,523	3,506	3,403
HEATING ONLY (EN14511 VALUE)											
Total heating capacity	(2)(3)	kW	46,60	53,40	60,80	67,60	75,50	90,40	115,6	145,3	178,0
COP	(2)(3)	kW/kW	3,400	3,440	3,430	3,450	3,480	3,490	3,490	3,470	3,370
COOLING WITH TOTAL HEAT RECOVERY											
Cooling capacity	(4)	kW	44,00	51,12	58,91	64,26	73,07	86,88	111,9	139,7	176,5
Total power input	(4)	kW	11,56	13,39	15,74	17,32	19,83	23,44	30,46	39,51	50,69
Recovery heat exchanger capacity	(4)	kW	54,86	63,71	73,71	80,54	91,71	108,9	140,5	176,8	224,1
TER		kW/kW	8,526	8,567	8,446	8,370	8,323	8,368	8,275	8,013	7,901
ENERGY EFFICIENCY											
SEASONAL EFFICIENCY IN COOLING (Reg. EU 2016/2281)											
Ambient refrigeration											
Prated,c	(11)	kW	-	-	-	-	-	-	-	-	-
SEER	(11)(12)		-	-	-	-	-	-	-	-	-
Performance ηs	(11)(13)	%	-	-	-	-	-	-	-	-	-
SEASONAL EFFICIENCY IN HEATING (Reg. EU 813/2013)											
PDesign	(5)	kW	33,2	38,2	43,6	49,4	55,6	65,8	83,0	106	135
SCOP	(5)(14)		3,59	3,60	3,63	3,75	3,77	3,71	3,69	3,66	3,64
Performance ηs	(5)(15)	%	141	141	142	147	148	145	144	143	143
Seasonal efficiency class	(16)		A+	A+	A+	A+	A+	A+	-	-	-
EXCHANGERS											
HEAT EXCHANGER USER SIDE IN REFRIGERATION											
Water flow	(1)	l/s	2,101	2,432	2,780	3,062	3,422	4,090	5,292	6,592	8,061
Pressure drop	(1)	kPa	14,7	19,7	15,8	19,2	17,1	19,4	22,3	26,2	31,8
HEAT EXCHANGER USER SIDE IN HEATING											
Water flow	(3)	l/s	2,242	2,567	2,927	3,249	3,629	4,349	5,563	6,992	8,561
Pressure drop	(3)	kPa	16,7	21,9	17,5	21,6	19,3	21,9	24,6	29,5	35,9
REFRIGERANT CIRCUIT											
Compressors nr.		N°	2	2	2	2	2	2	2	2	2
No. Circuits		N°	2	2	2	2	2	2	2	2	2
Refrigerant charge		kg	20,8	22,4	22,9	30,2	30,9	37,1	53,5	64,8	64,9
NOISE LEVEL											
Sound Pressure	(6)	dB(A)	53	53	53	53	53	54	55	56	56
Sound power level in cooling	(7)(8)	dB(A)	85	85	85	85	85	86	87	88	88
Sound power level in heating	(7)(9)	dB(A)	85	85	85	85	85	86	87	88	88
SIZE AND WEIGHT											
A	(10)	mm	2625	2625	2625	2625	2625	3250	3875	4500	4500
B	(10)	mm	1350	1350	1350	1350	1350	1350	1350	1350	1350
H	(10)	mm	2070	2070	2070	2070	2070	2070	2070	2070	2070
Operating weight	(10)	kg	850	870	890	960	970	1130	1430	1670	1730

Notes

- Plant (side) cooling exchanger water (in/out) 12°C/7°C; Source (side) heat exchanger air (in) 35°C.
- Values in compliance with EN14511
- Plant (side) heat exchanger water (in/out) 40°C/45°C; Source (side) heat exchanger air (in) 7°C - 87% R.H.
- Plant (side) cooling exchanger water (in/out) 12°C/7°C; Plant (side) heat exchanger water (in/out) 40°C/45°C.
- Parameter calculated for LOW-TEMPERATURE application in AVERAGE climate conditions according to [REGULATION (EU) N. 813/2013]
- Average sound pressure level at 10m distance, unit in a free field on a reflective surface; non-binding value calculated from the sound power level.
- Sound power on the basis of measurements made in compliance with ISO 9614.
- Sound power level in cooling, outdoors.
- Sound power level in heating, outdoors.
- Unit in standard configuration/execution, without optional accessories.
- Parameter calculated according to [REGULATION (EU) N. 2016/2281]
- Seasonal energy efficiency ratio
- Seasonal space cooling energy efficiency
- Seasonal coefficient of performance
- Seasonal space heating energy efficiency
- Energy efficiency class referred to LOW-TEMPERATURE application in AVERAGE climate conditions according to [REGULATION (EU) N. 811/2013]

The units highlighted in this publication contain HFC R410A [GWP₁₀₀ 2088] fluorinated greenhouse gases.
Certified data in EUROVENT

NX-Q /SL		0152P	0182P	0202P	0252P	0262P	0302P	0402P	0502P	
Power supply		V/ph/Hz 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50								
PERFORMANCE										
COOLING ONLY (GROSS VALUE)										
Cooling capacity	(1)	kW	43,20	49,82	58,48	63,18	71,56	84,78	108,5	130,7
Total power input	(1)	kW	12,48	14,69	17,25	19,36	22,03	25,52	33,44	44,29
EER	(1)	kW/kW	3,456	3,388	3,382	3,258	3,255	3,325	3,249	2,950
COOLING ONLY (EN14511 VALUE)										
Cooling capacity	(1)(2)	kW	43,10	49,60	58,30	63,00	71,40	84,50	108,2	130,3
EER	(1)(2)	kW/kW	3,420	3,330	3,330	3,210	3,220	3,280	3,210	2,910
ESEER	(1)(2)	kW/kW	4,240	4,130	4,140	4,070	4,030	4,060	4,000	3,680
HEATING ONLY (GROSS VALUE)										
Total heating capacity	(3)	kW	46,53	53,32	62,15	67,14	76,80	91,15	116,3	141,2
Total power input	(3)	kW	12,89	14,71	17,33	19,05	21,28	25,19	32,31	40,01
COP	(3)	kW/kW	3,605	3,626	3,595	3,513	3,606	3,615	3,601	3,530
HEATING ONLY (EN14511 VALUE)										
Total heating capacity	(2)(3)	kW	46,70	53,50	62,40	67,40	77,10	91,40	116,7	141,7
COP	(2)(3)	kW/kW	3,560	3,590	3,560	3,470	3,570	3,580	3,570	3,500
COOLING WITH TOTAL HEAT RECOVERY										
Cooling capacity	(4)	kW	44,00	51,12	58,91	64,26	73,07	86,88	111,9	139,7
Total power input	(4)	kW	11,56	13,39	15,74	17,32	19,83	23,44	30,46	39,51
Recovery heat exchanger capacity	(4)	kW	54,86	63,71	73,71	80,54	91,71	108,9	140,5	176,8
TER		kW/kW	8,526	8,567	8,446	8,370	8,323	8,368	8,275	8,013
ENERGY EFFICIENCY										
SEASONAL EFFICIENCY IN COOLING (Reg. EU 2016/2281)										
Ambient refrigeration										
Prated,c	(11)	kW	-	-	-	-	-	-	-	-
SEER	(11)(12)		-	-	-	-	-	-	-	-
Performance ηs	(11)(13)	%	-	-	-	-	-	-	-	-
SEASONAL EFFICIENCY IN HEATING (Reg. EU 813/2013)										
PDesign	(5)	kW	33,2	38,6	45,5	48,9	56,4	66,7	84,3	105
SCOP	(5)(14)		3,81	3,81	3,80	3,78	3,88	3,83	3,82	3,75
Performance ηs	(5)(15)	%	150	150	149	148	152	150	150	147
Seasonal efficiency class	(16)		A++	A++	A+	A+	A++	A++	-	-
EXCHANGERS										
HEAT EXCHANGER USER SIDE IN REFRIGERATION										
Water flow	(1)	l/s	2,066	2,382	2,797	3,021	3,422	4,054	5,188	6,252
Pressure drop	(1)	kPa	14,2	18,9	16,0	18,7	17,1	19,0	21,4	23,6
HEAT EXCHANGER USER SIDE IN HEATING										
Water flow	(3)	l/s	2,246	2,574	3,000	3,241	3,707	4,400	5,615	6,818
Pressure drop	(3)	kPa	16,8	22,1	18,4	21,5	20,1	22,4	25,1	28,0
REFRIGERANT CIRCUIT										
Compressors nr.		N°	2	2	2	2	2	2	2	2
No. Circuits		N°	2	2	2	2	2	2	2	2
Refrigerant charge		kg	27,1	28,7	28,8	29,9	42,0	48,9	63,1	63,2
NOISE LEVEL										
Sound Pressure	(6)	dB(A)	47	47	48	48	48	49	50	52
Sound power level in cooling	(7)(8)	dB(A)	79	79	80	80	80	81	82	84
Sound power level in heating	(7)(9)	dB(A)	79	79	80	80	80	81	82	84
SIZE AND WEIGHT										
A	(10)	mm	2625	2625	3250	3250	3250	3875	4500	4500
B	(10)	mm	1350	1350	1350	1350	1350	1350	1350	1350
H	(10)	mm	2070	2070	2070	2070	2070	2070	2070	2070
Operating weight	(10)	kg	890	910	1000	1030	1090	1270	1610	1680

Notes

- Plant (side) cooling exchanger water (in/out) 12°C/7°C; Source (side) heat exchanger air (in) 35°C.
- Values in compliance with EN14511
- Plant (side) heat exchanger water (in/out) 40°C/45°C; Source (side) heat exchanger air (in) 7°C - 87% R.H.
- Plant (side) cooling exchanger water (in/out) 12°C/7°C; Plant (side) heat exchanger water (in/out) 40°C/45°C.
- Parameter calculated for LOW-TEMPERATURE application in AVERAGE climate conditions according to [REGULATION (EU) N. 813/2013]
- Average sound pressure level at 10m distance, unit in a free field on a reflective surface; non-binding value calculated from the sound power level.
- Sound power on the basis of measurements made in compliance with ISO 9614.
- Sound power level in cooling, outdoors.
- Sound power level in heating, outdoors.
- Unit in standard configuration/execution, without optional accessories.
- Parameter calculated according to [REGULATION (EU) N. 2016/2281]
- Seasonal energy efficiency ratio
- Seasonal space cooling energy efficiency
- Seasonal coefficient of performance
- Seasonal space heating energy efficiency
- Energy efficiency class referred to LOW-TEMPERATURE application in AVERAGE climate conditions according to [REGULATION (EU) N. 811/2013]

The units highlighted in this publication contain HFC R410A [GWP₁₀₀ 2088] fluorinated greenhouse gases.
 Certified data in EUROVENT

Dimensional drawing

