



**a-LIFE2 HP** are professional high-head fan coils by Climaveneta. The enhanced motor and the built-in version make these units ideal for ducted systems in tertiary and commercial sectors.

#### Control

PSW wall mounted controller

3 fan speeds and 3 operating modes manual switch, ON/OFF valve unit control. Remote water temperature probe.

MTW wall mounted thermostat

3 fan speeds and 3 operating modes manual switch, ON/OFF valve unit control. Room air temperature probe and remote water temperature probe.

ATW wall mounted thermostat

Operating modes selection and fan speed control (Max/Med/Min/AUTO). Room air temperature probe and remote water temperature probe. ON/OFF valve unit control. Electric heater control (ATW only). Configurable digital input. TTL serial port (Modbus RTU) for installation in BMS systems (BusAdapter required).

EKW wall mounted thermostat (with HB/ i-HB power board)

Operating modes selection and fan speed control. Room air temperature probe and remote water temperature probe. ON/OFF or modulating valve unit control. Electric heater control. Installation in BMS (e.g. Idrorelax). Installation management of Master-Slave system up to 8 fan-coil units.

iKW wall mounted programmable thermostat with LCD screen (with HB/i-HB power board)

Programmable room thermostat with operating modes selection and fan speed control. Room air temperature probe and remote water temperature probe. ON/OFF or modulating valve unit control. Electric heater control. Installation in BMS (e.g. Idrorelax). Installation management of Master-Slave system up to 8 fan-coil units.

IR Remote control (with HB/i-HB power board)

Set-point regulation, operating mode (OFF/COOLING/HEATING/AUTO /VENTILATION) and fan speed control (Max, Med, Min, AUTO).

#### Versions

DFIO built-in version, front air intake, horizontal installation  
DFIV built-in version, front air intake, vertical installation

DLIO built-in version, low air intake, horizontal installation  
DLIV built-in version, low air intake, vertical installation.

#### Features

High pressure centrifugal fan unit for ducted system.  
Multi speed directly coupled electric motor;  
Configurations for 2 and 4 pipe Systems.  
Structure in hot galvanised steel for maximum resistance to rust;  
Left-hand water connections, easy convertible into right-hand, by simply turning the coil.  
Air filter on all models.  
Auxiliary drain pan with thermal insulation for all Horizontal versions, made of galvanized steel.  
Plastic drain pan for all versions.

#### Accessories

- Hot water coil kit
- Main coil 2-way/3-way valve unit
- 2 & 3 Way Valves for main and additional coil with ON/OFF, PWM, 0-10V or 3P Motor.
- Kit control board to manage 0-10V or 3 points modulating valve unit
- Kit RS485 - interface for Building Management System
- Kit Bus Adapter for BMS
- Kit Gateway interface for MyHome Bticino System, in combination with i(HB) Powerboard and Controls EK/EKW e IK.
- Interface SPB Kit
- Heating element kit
- Condensate drain pump
- Horizontal and vertical fan coil auxiliary tray
- Hose kit
- Straight and angular (90°) plenum kits for air inlet
- Plenum kit with round, straight or 90° air ducts.

| a-LIFE2 HP DFIV/DLIV                  | 0302      | 0402     | 0502     | 0602     | 0702     |
|---------------------------------------|-----------|----------|----------|----------|----------|
| <b>ELECTRICAL DATA</b>                |           |          |          |          |          |
| Power supply                          | V/ph/Hz   | 230/1/50 | 230/1/50 | 230/1/50 | 230/1/50 |
| <b>2 PIPES SYSTEM CONFIGURATION</b>   |           |          |          |          |          |
| <b>ENERGY EFFICIENCY</b>              |           |          |          |          |          |
| <b>COOLING (EN14511 VALUE)</b>        |           |          |          |          |          |
| FCEER                                 | (1)(6)    | kW/kW    | 37       | 40       | 58       |
| FCEER Class                           |           |          | E        | E        | D        |
| <b>HEATING ONLY (EN14511 VALUE)</b>   |           |          |          |          |          |
| FCCOP                                 | (2)(6)    | kW/kW    | 41       | 45       | 65       |
| FCCOP Class                           |           |          | E        | E        | E        |
| <b>PERFORMANCE</b>                    |           |          |          |          |          |
| <b>MIN SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 52,0     | 52,0     | 38,0     |
| Air flow rate                         | (1)       | m³/h     | 392      | 435      | 464      |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 2,08     | 2,21     | 2,28     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 2,03     | 2,16     | 2,24     |
| Sensible capacity in cooling mode     | (1)       | kW       | 1,69     | 1,82     | 1,71     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 1,64     | 1,77     | 1,67     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,39     | 0,39     | 0,57     |
| Max water flow                        | (1)       | l/s      | 0,10     | 0,11     | 0,11     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 19,6     | 16,8     | 4,5      |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 2,33     | 2,48     | 2,55     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 2,38     | 2,53     | 2,59     |
| Water flow in heating mode            | (2)       | l/s      | 0,11     | 0,12     | 0,12     |
| Pressure drop in heating mode         | (2)       | kPa      | 18,2     | 19,2     | 5,1      |
| Sound Pressure                        | (3)       | dB(A)    | 42       | 45       | 34       |
| Sound Power                           | (4)(7)    | dB(A)    | 51       | 54       | 43       |
| <b>MED SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 71,0     | 71,0     | 53,0     |
| Air flow rate                         | (1)       | m³/h     | 500      | 555      | 525      |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 2,31     | 2,70     | 3,04     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 2,24     | 2,63     | 2,99     |
| Sensible capacity in cooling mode     | (1)       | kW       | 1,90     | 2,24     | 2,31     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 1,83     | 2,17     | 2,25     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,41     | 0,46     | 0,73     |
| Max water flow                        | (1)       | l/s      | 0,11     | 0,13     | 0,15     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 24,2     | 25,1     | 8,0      |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 2,59     | 3,03     | 3,40     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 2,66     | 3,10     | 3,46     |
| Water flow in heating mode            | (2)       | l/s      | 0,13     | 0,15     | 0,16     |
| Pressure drop in heating mode         | (2)       | kPa      | 22,2     | 28,0     | 8,8      |
| Sound Pressure                        | (3)       | dB(A)    | 45       | 52       | 41       |
| Sound Power                           | (4)(7)    | dB(A)    | 54       | 61       | 50       |
| <b>MAX SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 95,0     | 95,0     | 75,0     |
| Air flow rate                         | (1)       | m³/h     | 561      | 623      | 705      |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 2,88     | 3,28     | 3,74     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 2,79     | 3,19     | 3,67     |
| Sensible capacity in cooling mode     | (1)       | kW       | 2,39     | 2,77     | 2,93     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 2,30     | 2,67     | 2,85     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,49     | 0,51     | 0,81     |
| Max water flow                        | (1)       | l/s      | 0,14     | 0,16     | 0,18     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 37,9     | 37,0     | 12,2     |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 3,23     | 3,67     | 4,19     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 3,33     | 3,77     | 4,27     |
| Water flow in heating mode            | (2)       | l/s      | 0,16     | 0,18     | 0,20     |
| Pressure drop in heating mode         | (2)       | kPa      | 33,9     | 40,5     | 13,1     |
| Sound Pressure                        | (3)       | dB(A)    | 52       | 56       | 47       |
| Sound Power                           | (4)(7)    | dB(A)    | 61       | 65       | 56       |
| <b>SIZE AND WEIGHT</b>                |           |          |          |          |          |
| A                                     | (5)       | mm       | 650      | 650      | 850      |
| B                                     | (5)       | mm       | 215      | 215      | 215      |
| H                                     | (5)       | mm       | 450      | 450      | 450      |
| Operating weight                      | (5)       | kg       | 14       | 15       | 20       |
| Sound Power                           | (4)(7)    | dB(A)    | 61       | 65       | 60       |
| Sound Power                           | (4)(7)    | dB(A)    | 61       | 65       | 61       |

#### Notes

- 1 Room temperature 27 °C d.b./19 °C w.b.; Chilled water (in/out) 7/12 °C.
- 2 Room temperature 20 °C d.b.; Hot water (in/out) 45/40 °C
- 3 Sound pressure level in free field on a reflective surface, 1 m from fan front and 1 m from the ground. Non-binding value obtained from sound power level.
- 4 Sound power on the basis of measurements made in compliance with ISO 3741 and Eurovent 8/2.

5 Unit in standard configuration/execution, without optional accessories.

6 Values in compliance with EN14511

7 Values in compliance with [REGULATION (EU) N. 2016/2281]

Certified data in EUROVENT

| a-LIFE2 HP DFIV/DLIV                  | 0802      | 0902     | 1002     | 1102     | 1202     |
|---------------------------------------|-----------|----------|----------|----------|----------|
| <b>ELECTRICAL DATA</b>                |           |          |          |          |          |
| Power supply                          | V/ph/Hz   | 230/1/50 | 230/1/50 | 230/1/50 | 230/1/50 |
| <b>2 PIPES SYSTEM CONFIGURATION</b>   |           |          |          |          |          |
| <b>ENERGY EFFICIENCY</b>              |           |          |          |          |          |
| <b>COOLING (EN14511 VALUE)</b>        |           |          |          |          |          |
| FCEER                                 | (1)(6)    | kW/kW    | 49       | 43       | 48       |
| FCEER Class                           |           |          | E        | E        | E        |
| <b>HEATING ONLY (EN14511 VALUE)</b>   |           |          |          |          |          |
| FCCOP                                 | (2)(6)    | kW/kW    | 55       | 48       | 53       |
| FCCOP Class                           |           |          | E        | E        | E        |
| <b>PERFORMANCE</b>                    |           |          |          |          |          |
| <b>MIN SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 67,0     | 112      | 112      |
| Air flow rate                         | (1)       | m³/h     | 649      | 923      | 1026     |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 3,50     | 4,83     | 5,40     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 3,43     | 4,72     | 5,29     |
| Sensible capacity in cooling mode     | (1)       | kW       | 2,78     | 3,88     | 4,42     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 2,71     | 3,77     | 4,31     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,72     | 0,95     | 0,98     |
| Max water flow                        | (1)       | l/s      | 0,17     | 0,23     | 0,26     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 13,0     | 20,4     | 28,0     |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 3,93     | 5,42     | 6,05     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 3,99     | 5,53     | 6,16     |
| Water flow in heating mode            | (2)       | l/s      | 0,19     | 0,26     | 0,29     |
| Pressure drop in heating mode         | (2)       | kPa      | 11,8     | 23,4     | 28,1     |
| Sound Pressure                        | (3)       | dB(A)    | 41       | 47       | 51       |
| Sound Power                           | (4)(7)    | dB(A)    | 50       | 56       | 60       |
| <b>MED SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 96,0     | 135      | 135      |
| Air flow rate                         | (1)       | m³/h     | 852      | 1078     | 1198     |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 4,49     | 5,70     | 6,25     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 4,40     | 5,57     | 6,12     |
| Sensible capacity in cooling mode     | (1)       | kW       | 3,74     | 4,67     | 5,15     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 3,64     | 4,53     | 5,01     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,75     | 1,03     | 1,10     |
| Max water flow                        | (1)       | l/s      | 0,21     | 0,27     | 0,30     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 21,5     | 28,3     | 37,4     |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 5,03     | 6,39     | 7,00     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 5,13     | 6,53     | 7,14     |
| Water flow in heating mode            | (2)       | l/s      | 0,24     | 0,31     | 0,34     |
| Pressure drop in heating mode         | (2)       | kPa      | 18,8     | 31,7     | 36,8     |
| Sound Pressure                        | (3)       | dB(A)    | 49       | 51       | 54       |
| Sound Power                           | (4)(7)    | dB(A)    | 58       | 60       | 63       |
| <b>MAX SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 132      | 149      | 149      |
| Air flow rate                         | (1)       | m³/h     | 1116     | 1390     | 1544     |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 5,20     | 6,20     | 7,20     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 5,07     | 6,05     | 7,05     |
| Sensible capacity in cooling mode     | (1)       | kW       | 4,44     | 5,14     | 5,91     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 4,31     | 4,99     | 5,76     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,76     | 1,06     | 1,29     |
| Max water flow                        | (1)       | l/s      | 0,25     | 0,30     | 0,34     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 28,8     | 33,5     | 49,6     |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 5,83     | 6,95     | 8,07     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 5,97     | 7,10     | 8,22     |
| Water flow in heating mode            | (2)       | l/s      | 0,28     | 0,34     | 0,39     |
| Pressure drop in heating mode         | (2)       | kPa      | 24,8     | 37,0     | 47,8     |
| Sound Pressure                        | (3)       | dB(A)    | 55       | 54       | 59       |
| Sound Power                           | (4)(7)    | dB(A)    | 64       | 63       | 68       |
| <b>SIZE AND WEIGHT</b>                |           |          |          |          |          |
| A                                     | (5)       | mm       | 1050     | 1250     | 1250     |
| B                                     | (5)       | mm       | 215      | 215      | 215      |
| H                                     | (5)       | mm       | 450      | 450      | 450      |
| Operating weight                      | (5)       | kg       | 25       | 28       | 29       |
| Sound Power                           | (4)(7)    | dB(A)    | 64       | 63       | 66       |

**Notes**

- 1 Room temperature 27 °C d.b./19 °C w.b.; Chilled water (in/out) 7/12 °C.  
 2 Room temperature 20 °C d.b.; Hot water (in/out) 45/40 °C  
 3 Sound pressure level in free field on a reflective surface, 1 m from fan front and 1 m from the ground. Non-binding value obtained from sound power level.  
 4 Sound power on the basis of measurements made in compliance with ISO 3741 and Eurovent 8/2.

5 Unit in standard configuration/execution, without optional accessories.

6 Values in compliance with EN14511

7 Values in compliance with [REGULATION (EU) N. 2016/2281]

Certified data in EUROVENT

| a-LIFE2 HP DFIO/DLIO                  | 0302      | 0402     | 0502     | 0602     | 0702     |
|---------------------------------------|-----------|----------|----------|----------|----------|
| <b>ELECTRICAL DATA</b>                |           |          |          |          |          |
| Power supply                          | V/ph/Hz   | 230/1/50 | 230/1/50 | 230/1/50 | 230/1/50 |
| <b>2 PIPES SYSTEM CONFIGURATION</b>   |           |          |          |          |          |
| <b>ENERGY EFFICIENCY</b>              |           |          |          |          |          |
| <b>COOLING (EN14511 VALUE)</b>        |           |          |          |          |          |
| FCEER                                 | (1)(6)    | kW/kW    | 37       | 40       | 58       |
| FCEER Class                           |           |          | E        | E        | D        |
| <b>HEATING ONLY (EN14511 VALUE)</b>   |           |          |          |          |          |
| FCCOP                                 | (2)(6)    | kW/kW    | 41       | 45       | 65       |
| FCCOP Class                           |           |          | E        | E        | E        |
| <b>PERFORMANCE</b>                    |           |          |          |          |          |
| <b>MIN SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 52,0     | 52,0     | 38,0     |
| Air flow rate                         | (1)       | m³/h     | 392      | 435      | 464      |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 2,08     | 2,21     | 2,28     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 2,03     | 2,16     | 2,24     |
| Sensible capacity in cooling mode     | (1)       | kW       | 1,69     | 1,82     | 1,71     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 1,64     | 1,77     | 1,67     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,39     | 0,39     | 0,57     |
| Max water flow                        | (1)       | l/s      | 0,10     | 0,11     | 0,11     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 19,6     | 16,8     | 4,5      |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 2,33     | 2,48     | 2,55     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 2,38     | 2,53     | 2,59     |
| Water flow in heating mode            | (2)       | l/s      | 0,11     | 0,12     | 0,12     |
| Pressure drop in heating mode         | (2)       | kPa      | 18,2     | 19,2     | 5,1      |
| Sound Pressure                        | (3)       | dB(A)    | 42       | 45       | 34       |
| Sound Power                           | (4)(7)    | dB(A)    | 51       | 54       | 43       |
| <b>MED SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 71,0     | 71,0     | 53,0     |
| Air flow rate                         | (1)       | m³/h     | 500      | 555      | 525      |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 2,31     | 2,70     | 3,04     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 2,24     | 2,63     | 2,99     |
| Sensible capacity in cooling mode     | (1)       | kW       | 1,90     | 2,24     | 2,31     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 1,83     | 2,17     | 2,25     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,41     | 0,46     | 0,73     |
| Max water flow                        | (1)       | l/s      | 0,11     | 0,13     | 0,15     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 24,2     | 25,1     | 8,0      |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 2,59     | 3,03     | 3,40     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 2,66     | 3,10     | 3,46     |
| Water flow in heating mode            | (2)       | l/s      | 0,13     | 0,15     | 0,16     |
| Pressure drop in heating mode         | (2)       | kPa      | 22,2     | 28,0     | 8,8      |
| Sound Pressure                        | (3)       | dB(A)    | 45       | 52       | 41       |
| Sound Power                           | (4)(7)    | dB(A)    | 54       | 61       | 50       |
| <b>MAX SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 95,0     | 95,0     | 75,0     |
| Air flow rate                         | (1)       | m³/h     | 561      | 623      | 705      |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 2,88     | 3,28     | 3,74     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 2,79     | 3,19     | 3,67     |
| Sensible capacity in cooling mode     | (1)       | kW       | 2,39     | 2,77     | 2,93     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 2,30     | 2,67     | 2,85     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,49     | 0,51     | 0,81     |
| Max water flow                        | (1)       | l/s      | 0,14     | 0,16     | 0,18     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 37,9     | 37,0     | 12,2     |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 3,23     | 3,67     | 4,19     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 3,33     | 3,77     | 4,27     |
| Water flow in heating mode            | (2)       | l/s      | 0,16     | 0,18     | 0,20     |
| Pressure drop in heating mode         | (2)       | kPa      | 33,9     | 40,5     | 13,1     |
| Sound Pressure                        | (3)       | dB(A)    | 52       | 56       | 47       |
| Sound Power                           | (4)(7)    | dB(A)    | 61       | 65       | 56       |
| <b>SIZE AND WEIGHT</b>                |           |          |          |          |          |
| A                                     | (5)       | mm       | 745      | 745      | 945      |
| B                                     | (5)       | mm       | 215      | 215      | 215      |
| H                                     | (5)       | mm       | 450      | 450      | 450      |
| Operating weight                      | (5)       | kg       | 14       | 15       | 20       |
| Sound Power                           | (4)(7)    | dB(A)    | 61       | 65       | 60       |
| Sound Power                           | (4)(7)    | dB(A)    | 61       | 65       | 61       |

#### Notes

- 1 Room temperature 27 °C d.b./19 °C w.b.; Chilled water (in/out) 7/12 °C.
- 2 Room temperature 20 °C d.b.; Hot water (in/out) 45/40 °C
- 3 Sound pressure level in free field on a reflective surface, 1 m from fan front and 1 m from the ground. Non-binding value obtained from sound power level.
- 4 Sound power on the basis of measurements made in compliance with ISO 3741 and Eurovent 8/2.

5 Unit in standard configuration/execution, without optional accessories.

6 Values in compliance with EN14511

7 Values in compliance with [REGULATION (EU) N. 2016/2281]

Certified data in EUROVENT

| a-LIFE2 HP DFIO/DLIO                  | 0802      | 0902     | 1002     | 1102     | 1202     |
|---------------------------------------|-----------|----------|----------|----------|----------|
| <b>ELECTRICAL DATA</b>                |           |          |          |          |          |
| Power supply                          | V/ph/Hz   | 230/1/50 | 230/1/50 | 230/1/50 | 230/1/50 |
| <b>2 PIPES SYSTEM CONFIGURATION</b>   |           |          |          |          |          |
| <b>ENERGY EFFICIENCY</b>              |           |          |          |          |          |
| <b>COOLING (EN14511 VALUE)</b>        |           |          |          |          |          |
| FCEER                                 | (1)(6)    | kW/kW    | 49       | 43       | 48       |
| FCEER Class                           |           |          | E        | E        | E        |
| <b>HEATING ONLY (EN14511 VALUE)</b>   |           |          |          |          |          |
| FCCOP                                 | (2)(6)    | kW/kW    | 55       | 48       | 53       |
| FCCOP Class                           |           |          | E        | E        | E        |
| <b>PERFORMANCE</b>                    |           |          |          |          |          |
| <b>MIN SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 67,0     | 112      | 112      |
| Air flow rate                         | (1)       | m³/h     | 649      | 923      | 1026     |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 3,50     | 4,83     | 5,40     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 3,43     | 4,72     | 5,29     |
| Sensible capacity in cooling mode     | (1)       | kW       | 2,78     | 3,88     | 4,42     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 2,71     | 3,77     | 4,31     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,72     | 0,95     | 0,98     |
| Max water flow                        | (1)       | l/s      | 0,17     | 0,23     | 0,26     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 13,0     | 20,4     | 28,0     |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 3,93     | 5,42     | 6,05     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 3,99     | 5,53     | 6,16     |
| Water flow in heating mode            | (2)       | l/s      | 0,19     | 0,26     | 0,29     |
| Pressure drop in heating mode         | (2)       | kPa      | 11,8     | 23,4     | 28,1     |
| Sound Pressure                        | (3)       | dB(A)    | 41       | 47       | 51       |
| Sound Power                           | (4)(7)    | dB(A)    | 50       | 56       | 60       |
| <b>MED SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 96,0     | 135      | 135      |
| Air flow rate                         | (1)       | m³/h     | 852      | 1078     | 1198     |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 4,49     | 5,70     | 6,25     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 4,40     | 5,57     | 6,12     |
| Sensible capacity in cooling mode     | (1)       | kW       | 3,74     | 4,67     | 5,15     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 3,64     | 4,53     | 5,01     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,75     | 1,03     | 1,10     |
| Max water flow                        | (1)       | l/s      | 0,21     | 0,27     | 0,30     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 21,5     | 28,3     | 37,4     |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 5,03     | 6,39     | 7,00     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 5,13     | 6,53     | 7,14     |
| Water flow in heating mode            | (2)       | l/s      | 0,24     | 0,31     | 0,34     |
| Pressure drop in heating mode         | (2)       | kPa      | 18,8     | 31,7     | 36,8     |
| Sound Pressure                        | (3)       | dB(A)    | 49       | 51       | 54       |
| Sound Power                           | (4)(7)    | dB(A)    | 58       | 60       | 63       |
| <b>MAX SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 132      | 149      | 149      |
| Air flow rate                         | (1)       | m³/h     | 1116     | 1390     | 1544     |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 5,20     | 6,20     | 7,20     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 5,07     | 6,05     | 7,05     |
| Sensible capacity in cooling mode     | (1)       | kW       | 4,44     | 5,14     | 5,91     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 4,31     | 4,99     | 5,76     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,76     | 1,06     | 1,29     |
| Max water flow                        | (1)       | l/s      | 0,25     | 0,30     | 0,34     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 28,8     | 33,5     | 49,6     |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 5,83     | 6,95     | 8,07     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 5,97     | 7,10     | 8,22     |
| Water flow in heating mode            | (2)       | l/s      | 0,28     | 0,34     | 0,39     |
| Pressure drop in heating mode         | (2)       | kPa      | 24,8     | 37,0     | 47,8     |
| Sound Pressure                        | (3)       | dB(A)    | 55       | 54       | 59       |
| Sound Power                           | (4)(7)    | dB(A)    | 64       | 63       | 68       |
| <b>SIZE AND WEIGHT</b>                |           |          |          |          |          |
| A                                     | (5)       | mm       | 1145     | 1345     | 1345     |
| B                                     | (5)       | mm       | 215      | 215      | 215      |
| H                                     | (5)       | mm       | 450      | 450      | 450      |
| Operating weight                      | (5)       | kg       | 25       | 28       | 29       |
| Sound Power                           | (4)(7)    | dB(A)    | 64       | 63       | 66       |

**Notes**

- 1 Room temperature 27 °C d.b./19 °C w.b.; Chilled water (in/out) 7/12 °C.  
 2 Room temperature 20 °C d.b.; Hot water (in/out) 45/40 °C  
 3 Sound pressure level in free field on a reflective surface, 1 m from fan front and 1 m from the ground. Non-binding value obtained from sound power level.  
 4 Sound power on the basis of measurements made in compliance with ISO 3741 and Eurovent 8/2.

5 Unit in standard configuration/execution, without optional accessories.

6 Values in compliance with EN14511

7 Values in compliance with [REGULATION (EU) N. 2016/2281]

Certified data in EUROVENT

| a-LIFE2 HP DFIV/DLIV                  | 0304      | 0404     | 0504     | 0604     | 0704     |
|---------------------------------------|-----------|----------|----------|----------|----------|
| <b>ELECTRICAL DATA</b>                |           |          |          |          |          |
| Power supply                          | V/ph/Hz   | 230/1/50 | 230/1/50 | 230/1/50 | 230/1/50 |
| <b>4 PIPES SYSTEM CONFIGURATION</b>   |           |          |          |          |          |
| <b>ENERGY EFFICIENCY</b>              |           |          |          |          |          |
| <b>COOLING (EN14511 VALUE)</b>        |           |          |          |          |          |
| FCEER                                 | (1)(6)    | kW/kW    | 36       | 40       | 58       |
| FCEER Class                           |           |          | E        | E        | D        |
| <b>HEATING ONLY (EN14511 VALUE)</b>   |           |          |          |          |          |
| FCCOP                                 | (2)(6)    | kW/kW    | 30       | 29       | 46       |
| FCCOP Class                           |           |          | E        | E        | E        |
| <b>PERFORMANCE</b>                    |           |          |          |          |          |
| <b>MIN SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 52,0     | 52,0     | 38,0     |
| Air flow rate                         | (1)       | m³/h     | 392      | 435      | 464      |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 2,08     | 2,21     | 2,28     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 2,03     | 2,16     | 2,24     |
| Sensible capacity in cooling mode     | (1)       | kW       | 1,69     | 1,82     | 1,84     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 1,64     | 1,77     | 1,80     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,39     | 0,39     | 0,44     |
| Max water flow                        | (1)       | l/s      | 0,10     | 0,11     | 0,11     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 19,6     | 16,8     | 4,5      |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 1,50     | 1,59     | 1,78     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 1,55     | 1,64     | 1,82     |
| Water flow in heating mode            | (2)       | l/s      | 0,04     | 0,04     | 0,04     |
| Pressure drop in heating mode         | (2)       | kPa      | 5,8      | 6,5      | 8,3      |
| Sound Pressure                        | (3)       | dB(A)    | 42       | 45       | 34       |
| Sound Power                           | (4)(7)    | dB(A)    | 51       | 54       | 43       |
| <b>MED SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 71,0     | 71,0     | 53,0     |
| Air flow rate                         | (1)       | m³/h     | 500      | 555      | 525      |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 2,31     | 2,70     | 3,04     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 2,24     | 2,63     | 2,99     |
| Sensible capacity in cooling mode     | (1)       | kW       | 1,90     | 2,24     | 2,48     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 1,83     | 2,17     | 2,43     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,41     | 0,46     | 0,56     |
| Max water flow                        | (1)       | l/s      | 0,11     | 0,13     | 0,15     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 24,2     | 25,1     | 8,0      |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 1,67     | 1,95     | 2,37     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 1,74     | 2,02     | 2,43     |
| Water flow in heating mode            | (2)       | l/s      | 0,04     | 0,05     | 0,06     |
| Pressure drop in heating mode         | (2)       | kPa      | 7,1      | 9,5      | 14,2     |
| Sound Pressure                        | (3)       | dB(A)    | 45       | 52       | 41       |
| Sound Power                           | (4)(7)    | dB(A)    | 54       | 61       | 50       |
| <b>MAX SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 95,0     | 95,0     | 75,0     |
| Air flow rate                         | (1)       | m³/h     | 561      | 623      | 705      |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 2,88     | 3,28     | 3,74     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 2,79     | 3,19     | 3,67     |
| Sensible capacity in cooling mode     | (1)       | kW       | 2,39     | 2,77     | 3,15     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 2,30     | 2,67     | 3,08     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,49     | 0,51     | 0,59     |
| Max water flow                        | (1)       | l/s      | 0,14     | 0,16     | 0,18     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 37,9     | 37,0     | 12,2     |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 2,08     | 2,36     | 2,92     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 2,17     | 2,46     | 3,00     |
| Water flow in heating mode            | (2)       | l/s      | 0,05     | 0,06     | 0,07     |
| Pressure drop in heating mode         | (2)       | kPa      | 10,8     | 13,8     | 21,0     |
| Sound Pressure                        | (3)       | dB(A)    | 52       | 56       | 47       |
| Sound Power                           | (4)(7)    | dB(A)    | 61       | 65       | 56       |
| <b>SIZE AND WEIGHT</b>                |           |          |          |          |          |
| A                                     | (5)       | mm       | 650      | 650      | 850      |
| B                                     | (5)       | mm       | 215      | 215      | 215      |
| H                                     | (5)       | mm       | 450      | 450      | 450      |
| Operating weight                      | (5)       | kg       | 15       | 16       | 21       |
| Sound Power                           | (4)(7)    | dB(A)    | 61       | 65       | 60       |
| Sound Power                           | (4)(7)    | dB(A)    | 61       | 65       | 61       |

#### Notes

- 1 Room temperature 27°C d.b./18,9°C w.b., Chilled water (in/out) 7°C/12°C.
- 2 Room temperature 20 °C d.b., hot water (in/out) 65/55 °C
- 3 Sound pressure level in free field on a reflective surface, 1 m from fan front and 1 m from the ground. Non-binding value obtained from sound power level.
- 4 Sound power on the basis of measurements made in compliance with ISO 3741 and Eurovent 8/2.

5 Unit in standard configuration/execution, without optional accessories.

6 Values in compliance with EN14511

7 Values in compliance with [REGULATION (EU) N. 2016/2281]

Certified data in EUROVENT

| a-LIFE2 HP DFIV/DLIV                  | 0804      | 0904     | 1004     | 1104     | 1204     |
|---------------------------------------|-----------|----------|----------|----------|----------|
| <b>ELECTRICAL DATA</b>                |           |          |          |          |          |
| Power supply                          | V/ph/Hz   | 230/1/50 | 230/1/50 | 230/1/50 | 230/1/50 |
| <b>4 PIPES SYSTEM CONFIGURATION</b>   |           |          |          |          |          |
| <b>ENERGY EFFICIENCY</b>              |           |          |          |          |          |
| <b>COOLING (EN14511 VALUE)</b>        |           |          |          |          |          |
| FCEER                                 | (1)(6)    | kW/kW    | 49       | 43       | 48       |
| FCEER Class                           |           |          | E        | E        | E        |
| <b>HEATING ONLY (EN14511 VALUE)</b>   |           |          |          |          |          |
| FCCOP                                 | (2)(6)    | kW/kW    | 35       | 30       | 34       |
| FCCOP Class                           |           |          | E        | E        | E        |
| <b>PERFORMANCE</b>                    |           |          |          |          |          |
| <b>MIN SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 67,0     | 112      | 112      |
| Air flow rate                         | (1)       | m³/h     | 649      | 923      | 1026     |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 3,50     | 4,83     | 5,40     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 3,43     | 4,72     | 5,29     |
| Sensible capacity in cooling mode     | (1)       | kW       | 2,78     | 3,88     | 4,42     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 2,71     | 3,77     | 4,31     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,72     | 0,95     | 0,98     |
| Max water flow                        | (1)       | l/s      | 0,17     | 0,23     | 0,26     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 13,0     | 20,8     | 28,0     |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 2,50     | 3,43     | 3,84     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 2,56     | 3,54     | 3,95     |
| Water flow in heating mode            | (2)       | l/s      | 0,06     | 0,08     | 0,09     |
| Pressure drop in heating mode         | (2)       | kPa      | 5,2      | 7,6      | 9,5      |
| Sound Pressure                        | (3)       | dB(A)    | 41       | 49       | 51       |
| Sound Power                           | (4)(7)    | dB(A)    | 50       | 58       | 60       |
| <b>MED SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 96,0     | 135      | 135      |
| Air flow rate                         | (1)       | m³/h     | 852      | 1078     | 1198     |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 4,49     | 5,70     | 6,25     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 4,40     | 5,57     | 6,12     |
| Sensible capacity in cooling mode     | (1)       | kW       | 3,74     | 4,67     | 5,15     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 3,64     | 4,53     | 5,01     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,75     | 1,03     | 1,10     |
| Max water flow                        | (1)       | l/s      | 0,21     | 0,27     | 0,30     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 21,5     | 28,9     | 37,4     |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 3,21     | 4,05     | 4,44     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 3,31     | 4,19     | 4,58     |
| Water flow in heating mode            | (2)       | l/s      | 0,08     | 0,10     | 0,11     |
| Pressure drop in heating mode         | (2)       | kPa      | 8,4      | 10,5     | 12,5     |
| Sound Pressure                        | (3)       | dB(A)    | 49       | 51       | 54       |
| Sound Power                           | (4)(7)    | dB(A)    | 58       | 60       | 63       |
| <b>MAX SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 132      | 149      | 149      |
| Air flow rate                         | (1)       | m³/h     | 1116     | 1390     | 1544     |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 5,20     | 6,20     | 7,20     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 5,07     | 6,05     | 7,05     |
| Sensible capacity in cooling mode     | (1)       | kW       | 4,44     | 5,14     | 5,91     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 4,31     | 4,99     | 5,76     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,76     | 1,06     | 1,29     |
| Max water flow                        | (1)       | l/s      | 0,25     | 0,30     | 0,34     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 28,8     | 34,2     | 49,6     |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 3,72     | 4,41     | 5,12     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 3,85     | 4,56     | 5,27     |
| Water flow in heating mode            | (2)       | l/s      | 0,09     | 0,11     | 0,12     |
| Pressure drop in heating mode         | (2)       | kPa      | 11,1     | 12,3     | 16,3     |
| Sound Pressure                        | (3)       | dB(A)    | 55       | 54       | 59       |
| Sound Power                           | (4)(7)    | dB(A)    | 64       | 63       | 68       |
| <b>SIZE AND WEIGHT</b>                |           |          |          |          |          |
| A                                     | (5)       | mm       | 1050     | 1250     | 1250     |
| B                                     | (5)       | mm       | 215      | 215      | 215      |
| H                                     | (5)       | mm       | 450      | 450      | 450      |
| Operating weight                      | (5)       | kg       | 26       | 29       | 31       |
| Sound Power                           | (4)(7)    | dB(A)    | 64       | 63       | 66       |

**Notes**

- 1 Room temperature 27°C d.b./18,9°C w.b., Chilled water (in/out) 7°C/12°C.  
 2 Room temperature 20 °C d.b., hot water (in/out) 65/55 °C  
 3 Sound pressure level in free field on a reflective surface, 1 m from fan front and 1 m from the ground. Non-binding value obtained from sound power level.  
 4 Sound power on the basis of measurements made in compliance with ISO 3741 and Eurovent 8/2.

5 Unit in standard configuration/execution, without optional accessories.

6 Values in compliance with EN14511

7 Values in compliance with [REGULATION (EU) N. 2016/2281]

Certified data in EUROVENT

| a-LIFE2 HP DFIO/DLIO                  | 0304      | 0404     | 0504     | 0604     | 0704     |
|---------------------------------------|-----------|----------|----------|----------|----------|
| <b>ELECTRICAL DATA</b>                |           |          |          |          |          |
| Power supply                          | V/ph/Hz   | 230/1/50 | 230/1/50 | 230/1/50 | 230/1/50 |
| <b>4 PIPES SYSTEM CONFIGURATION</b>   |           |          |          |          |          |
| <b>ENERGY EFFICIENCY</b>              |           |          |          |          |          |
| <b>COOLING (EN14511 VALUE)</b>        |           |          |          |          |          |
| FCEER                                 | (1)(6)    | kW/kW    | 36       | 40       | 58       |
| FCEER Class                           |           |          | E        | E        | D        |
| <b>HEATING ONLY (EN14511 VALUE)</b>   |           |          |          |          |          |
| FCCOP                                 | (2)(6)    | kW/kW    | 30       | 29       | 46       |
| FCCOP Class                           |           |          | E        | E        | E        |
| <b>PERFORMANCE</b>                    |           |          |          |          |          |
| <b>MIN SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 52,0     | 52,0     | 38,0     |
| Air flow rate                         | (1)       | m³/h     | 392      | 435      | 464      |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 2,08     | 2,21     | 2,28     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 2,03     | 2,16     | 2,24     |
| Sensible capacity in cooling mode     | (1)       | kW       | 1,69     | 1,82     | 1,84     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 1,64     | 1,77     | 1,80     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,39     | 0,39     | 0,44     |
| Max water flow                        | (1)       | l/s      | 0,10     | 0,11     | 0,11     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 19,6     | 16,8     | 4,5      |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 1,50     | 1,59     | 1,78     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 1,55     | 1,64     | 1,82     |
| Water flow in heating mode            | (2)       | l/s      | 0,04     | 0,04     | 0,04     |
| Pressure drop in heating mode         | (2)       | kPa      | 5,8      | 6,5      | 8,3      |
| Sound Pressure                        | (3)       | dB(A)    | 42       | 45       | 34       |
| Sound Power                           | (4)(7)    | dB(A)    | 51       | 54       | 43       |
| <b>MED SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 71,0     | 71,0     | 53,0     |
| Air flow rate                         | (1)       | m³/h     | 500      | 555      | 525      |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 2,31     | 2,70     | 3,04     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 2,24     | 2,63     | 2,99     |
| Sensible capacity in cooling mode     | (1)       | kW       | 1,90     | 2,24     | 2,48     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 1,83     | 2,17     | 2,43     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,41     | 0,46     | 0,56     |
| Max water flow                        | (1)       | l/s      | 0,11     | 0,13     | 0,15     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 24,2     | 25,1     | 8,0      |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 1,67     | 1,95     | 2,37     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 1,74     | 2,02     | 2,43     |
| Water flow in heating mode            | (2)       | l/s      | 0,04     | 0,05     | 0,06     |
| Pressure drop in heating mode         | (2)       | kPa      | 7,1      | 9,5      | 14,2     |
| Sound Pressure                        | (3)       | dB(A)    | 45       | 52       | 41       |
| Sound Power                           | (4)(7)    | dB(A)    | 54       | 61       | 50       |
| <b>MAX SPEED</b>                      |           |          |          |          |          |
| Fan Power Input                       | (1)       | W        | 95,0     | 95,0     | 75,0     |
| Air flow rate                         | (1)       | m³/h     | 561      | 623      | 705      |
| <b>Total capacity in cooling mode</b> | (1)       | kW       | 2,88     | 3,28     | 3,74     |
| <b>Total Net Cooling Capacity</b>     | (1)(6)(7) | kW       | 2,79     | 3,19     | 3,67     |
| Sensible capacity in cooling mode     | (1)       | kW       | 2,39     | 2,77     | 3,15     |
| Net sensible cooling capacity         | (1)(6)(7) | kW       | 2,30     | 2,67     | 3,08     |
| Net latent power in cooling           | (1)(6)(7) | kW       | 0,49     | 0,51     | 0,59     |
| Max water flow                        | (1)       | l/s      | 0,14     | 0,16     | 0,18     |
| Pressure Drop in cooling mode         | (1)       | kPa      | 37,9     | 37,0     | 12,2     |
| <b>Total capacity (heating mode)</b>  | (2)       | kW       | 2,08     | 2,36     | 2,92     |
| <b>Total Net Heating Capacity</b>     | (2)(6)    | kW       | 2,17     | 2,46     | 3,00     |
| Water flow in heating mode            | (2)       | l/s      | 0,05     | 0,06     | 0,07     |
| Pressure drop in heating mode         | (2)       | kPa      | 10,8     | 13,8     | 21,0     |
| Sound Pressure                        | (3)       | dB(A)    | 52       | 56       | 47       |
| Sound Power                           | (4)(7)    | dB(A)    | 61       | 65       | 56       |
| <b>SIZE AND WEIGHT</b>                |           |          |          |          |          |
| A                                     | (5)       | mm       | 745      | 745      | 945      |
| B                                     | (5)       | mm       | 215      | 215      | 215      |
| H                                     | (5)       | mm       | 450      | 450      | 450      |
| Operating weight                      | (5)       | kg       | 15       | 16       | 21       |
| Sound Power                           | (4)(7)    | dB(A)    | 61       | 65       | 60       |
| Sound Power                           | (4)(7)    | dB(A)    | 61       | 65       | 61       |

#### Notes

- 1 Room temperature 27°C d.b./18,9°C w.b., Chilled water (in/out) 7°C/12°C.
- 2 Room temperature 20 °C d.b., hot water (in/out) 65/55 °C
- 3 Sound pressure level in free field on a reflective surface, 1 m from fan front and 1 m from the ground. Non-binding value obtained from sound power level.
- 4 Sound power on the basis of measurements made in compliance with ISO 3741 and Eurovent 8/2.

5 Unit in standard configuration/execution, without optional accessories.

6 Values in compliance with EN14511

7 Values in compliance with [REGULATION (EU) N. 2016/2281]

Certified data in EUROVENT

| a-LIFE2 HP DFIO/DLIO   | 0804  | 0904     | 1004     | 1104     | 1204     |
|--|---|----------|----------|----------|----------|
| <b>ELECTRICAL DATA</b>   |   |          |          |          |          |
| Power supply   | V/ph/Hz   | 230/1/50 | 230/1/50 | 230/1/50 | 230/1/50 |
| <b>4 PIPES SYSTEM CONFIGURATION</b>  |   |          |          |          |          |
| <b>ENERGY EFFICIENCY</b>   |   |          |          |          |          |
| <b>COOLING (EN14511 VALUE)</b>   |   |          |          |          |          |
| FCEER  | (1)(6)  | kW/kW    | 49       | 43       | 48       |
| FCEER Class  |   |          | E        | E        | E        |
| <b>HEATING ONLY (EN14511 VALUE)</b>  |   |          |          |          |          |
| FCCOP  | (2)(6)  | kW/kW    | 35       | 30       | 34       |
| FCCOP Class  |   |          | E        | E        | E        |
| <b>PERFORMANCE</b>   |   |          |          |          |          |
| <b>MIN SPEED</b>   |   |          |          |          |          |
| Fan Power Input  | (1)   | W        | 67,0     | 112      | 112      |
| Air flow rate  | (1)   | m³/h     | 649      | 923      | 1026     |
| <b>Total capacity in cooling mode</b>  | (1)   | kW       | 3,50     | 4,83     | 5,40     |
| <b>Total Net Cooling Capacity</b>  | (1)(6)(7)   | kW       | 3,43     | 4,72     | 5,29     |
| Sensible capacity in cooling mode  | (1)   | kW       | 2,78     | 3,88     | 4,42     |
| Net sensible cooling capacity  | (1)(6)(7)   | kW       | 2,71     | 3,77     | 4,31     |
| Net latent power in cooling  | (1)(6)(7)   | kW       | 0,72     | 0,95     | 0,98     |
| Max water flow   | (1)   | l/s      | 0,17     | 0,23     | 0,26     |
| Pressure Drop in cooling mode  | (1)   | kPa      | 13,0     | 20,8     | 28,0     |
| <b>Total capacity (heating mode)</b>   | (2)   | kW       | 2,50     | 3,43     | 3,84     |
| <b>Total Net Heating Capacity</b>  | (2)(6)  | kW       | 2,56     | 3,54     | 3,95     |
| Water flow in heating mode   | (2)   | l/s      | 0,06     | 0,08     | 0,09     |
| Pressure drop in heating mode  | (2)   | kPa      | 5,2      | 7,6      | 9,5      |
| Sound Pressure   | (3)   | dB(A)    | 41       | 49       | 51       |
| Sound Power  | (4)(7)  | dB(A)    | 50       | 58       | 60       |
| <b>MED SPEED</b>   |   |          |          |          |          |
| Fan Power Input  | (1)   | W        | 96,0     | 135      | 135      |
| Air flow rate  | (1)   | m³/h     | 852      | 1078     | 1198     |
| <b>Total capacity in cooling mode</b>  | (1)   | kW       | 4,49     | 5,70     | 6,25     |
| <b>Total Net Cooling Capacity</b>  | (1)(6)(7)   | kW       | 4,40     | 5,57     | 6,12     |
| Sensible capacity in cooling mode  | (1)   | kW       | 3,74     | 4,67     | 5,15     |
| Net sensible cooling capacity  | (1)(6)(7)   | kW       | 3,64     | 4,53     | 5,01     |
| Net latent power in cooling  | (1)(6)(7)   | kW       | 0,75     | 1,03     | 1,10     |
| Max water flow   | (1)   | l/s      | 0,21     | 0,27     | 0,30     |
| Pressure Drop in cooling mode  | (1)   | kPa      | 21,5     | 28,9     | 37,4     |
| <b>Total capacity (heating mode)</b>   | (2)   | kW       | 3,21     | 4,05     | 4,44     |
| <b>Total Net Heating Capacity</b>  | (2)(6)  | kW       | 3,31     | 4,19     | 4,58     |
| Water flow in heating mode   | (2)   | l/s      | 0,08     | 0,10     | 0,11     |
| Pressure drop in heating mode  | (2)   | kPa      | 8,4      | 10,5     | 12,5     |
| Sound Pressure   | (3)   | dB(A)    | 49       | 51       | 54       |
| Sound Power  | (4)(7)  | dB(A)    | 58       | 60       | 63       |
| <b>MAX SPEED</b>   |   |          |          |          |          |
| Fan Power Input  | (1)   | W        | 132      | 149      | 149      |
| Air flow rate  | (1)   | m³/h     | 1116     | 1390     | 1544     |
| <b>Total capacity in cooling mode</b>  | (1)   | kW       | 5,20     | 6,20     | 7,20     |
| <b>Total Net Cooling Capacity</b>  | (1)(6)(7)   | kW       | 5,07     | 6,05     | 7,05     |
| Sensible capacity in cooling mode  | (1)   | kW       | 4,44     | 5,14     | 5,91     |
| Net sensible cooling capacity  | (1)(6)(7)   | kW       | 4,31     | 4,99     | 5,76     |
| Net latent power in cooling  | (1)(6)(7)   | kW       | 0,76     | 1,06     | 1,29     |
| Max water flow   | (1)   | l/s      | 0,25     | 0,30     | 0,34     |
| Pressure Drop in cooling mode  | (1)   | kPa      | 28,8     | 34,2     | 49,6     |
| <b>Total capacity (heating mode)</b>   | (2)   | kW       | 3,72     | 4,41     | 5,12     |
| <b>Total Net Heating Capacity</b>  | (2)(6)  | kW       | 3,85     | 4,56     | 5,27     |
| Water flow in heating mode   | (2)   | l/s      | 0,09     | 0,11     | 0,12     |
| Pressure drop in heating mode  | (2)   | kPa      | 11,1     | 12,3     | 16,3     |
| Sound Pressure   | (3)   | dB(A)    | 55       | 54       | 59       |
| Sound Power  | (4)(7)  | dB(A)    | 64       | 63       | 68       |
| <b>SIZE AND WEIGHT</b>   |   |          |          |          |          |
| A  | (5)   | mm       | 1145     | 1345     | 1345     |
| B  | (5)   | mm       | 215      | 215      | 215      |
| H  | (5)   | mm       | 450      | 450      | 450      |
| Operating weight   | (5)   | kg       | 27       | 29       | 31       |
| <b>Notes</b>   |   |          |          |          |          |
| 1 Room temperature 27°C d.b./18,9°C w.b., Chilled water (in/out) 7°C/12°C.   | 5 Unit in standard configuration/execution, without optional accessories. |          |          |          |          |
| 2 Room temperature 20 °C d.b., hot water (in/out) 65/55 °C   | 6 Values in compliance with EN14511                                       |          |          |          |          |
| 3 Sound pressure level in free field on a reflective surface, 1 m from fan front and 1 m from the ground. Non-binding value obtained from sound power level. | 7 Values in compliance with [REGULATION (EU) N. 2016/2281]                |          |          |          |          |
| 4 Sound power on the basis of measurements made in compliance with ISO 3741 and Eurovent 8/2.  |   |          |          |          |          |
| Certified data in EUROVENT   |   |          |          |          |          |

**Notes**

- 1 Room temperature 27°C d.b./18,9°C w.b., Chilled water (in/out) 7°C/12°C.  
 2 Room temperature 20 °C d.b., hot water (in/out) 65/55 °C  
 3 Sound pressure level in free field on a reflective surface, 1 m from fan front and 1 m from the ground. Non-binding value obtained from sound power level.  
 4 Sound power on the basis of measurements made in compliance with ISO 3741 and Eurovent 8/2.

5 Unit in standard configuration/execution, without optional accessories.

6 Values in compliance with EN14511

7 Values in compliance with [REGULATION (EU) N. 2016/2281]

### Dimensional drawing

