

High Head professional Fan-Coil with Brushless EC motor for continuous regulation of airflow and fan speed.



i-LIFE2 HP are the new high head Fan-Coil Climaveneta in built in version with EC Brushless motor. The continuous regulation of air flow and termal capacity, guarantees a total comfort and high energy saving. **i-LIFE2 HP** is the ideal solution for ducted systems and installations in tertiary and commercial sectors.

Control

ATW-EC wall mounted thermostat

Operating modes selection and fan speed control (0-10Vdc). Room air temperature probe and remote water temperature probe. ON/OFF valve unit control. Electric heater control (ATW-EC only). Configurable digital input.

EKW wall mounted thermostat (with HB/ i-HB power board) Operating modes selection and fan speed control. Room air temperature probe and remote water temperature probe. ON/OFF or modulating valve unit control. Electric heater control. Installation in BMS (e.g. Idrorelax). Installation management of Master-Slave system up to 8 fan-coil units.

iKW wall mounted programmable thermostat with LCD screen (with HB/i-HB power board)

Programmable room thermostat with operating modes selection and fan speed control. Room air temperature probe and remote water temperature probe. ON/OFF or modulating valve unit control. Electric heater control. Installation in BMS (e.g. Idrorelax). Installation management of Master-Slave system up to 8 fan-coil units.

IR Remote control (with HB/i-HB power board)

Set-point regulation, operating mode (OFF/COOLING/HEATING/AUTO /VENTILATION) and fan speed control (Max, Med, Min, AUTO).

Versions

DFIO built-in version, front air intake, horizontal installation
DFIV built-in version, front air intake, vertical installation

DLIO built-in version, low air intake, horizontal installation
DLIV built-in version, low air intake, vertical installation.

Features

High pressure centrifugal fan unit for ducted system.
High efficiency EC motor.
Modulating speed centrifugal fan and air flow regulation.
Energy consumption reduced by more than 50%
Coils with aluminium fins and copper pipes.
Configurations for 2 and 4 pipe Systems.
Left-hand water connections, easy convertible into right-hand, by simply turning the coil.
Air filter on all models.
Structure in galvanised steel of high thickness for maximum resistance to rust.
Auxiliary drain pan with thermal insulation for all Horizontal versions, made of galvanized steel.
Plastic drain pan for all versions.

Accessories

- Additional coil 2-way/3-way valve unit
- Main coil 2-way/3-way valve unit
- Hot water coil kit
- Kit control board to manage 0-10V or 3 points modulating valve unit
- Kit RS485 - interface for Building Management System
- Kit Gateway interface for MyHome Bticino System, in combination with i(HB) Powerboard and Controls EK/EKW e IK.
- Hose kit
- Plenum kit with round, straight or 90° air ducts.
- Kit i-HB powerboard for units with EC motor and IKW, EKW Controls
- Condensate drain pump with float switch supplied as standard.
- Horizontal and vertical fan coil auxiliary tray

i-LIFE2 HP DFIV/DLIV	0202	0402	0602	0802	1002	1202
ELECTRICAL DATA						
Power supply	V/ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
2 PIPES SYSTEM CONFIGURATION						
ENERGY EFFICIENCY						
COOLING (EN14511 VALUE)						
FCEER	(1)(6)	kW/kW	125	122	124	120
FCEER Class			B	B	B	B
HEATING ONLY (EN14511 VALUE)						
FCCOP	(2)(6)	kW/kW	141	162	173	165
FCCOP Class			C	B	B	B
PERFORMANCE						
MIN SPEED						
Fan Power Input	(1)	W	6,81	11,2	10,9	11,9
Air flow rate	(1)	m³/h	176	242	289	318
Total capacity in cooling mode	(1)	kW	1,00	1,50	1,95	2,35
Total Net Cooling Capacity	(1)(6)(7)	kW	0,99	1,49	1,94	2,33
Sensible capacity in cooling mode	(1)	kW	0,79	1,16	1,50	1,83
Net sensible cooling capacity	(1)(6)(7)	kW	0,78	1,15	1,49	1,82
Net latent power in cooling	(1)(6)(7)	kW	0,21	0,34	0,45	0,52
Max water flow	(1)	l/s	0,05	0,07	0,09	0,11
Pressure Drop in cooling mode	(1)	kPa	3,1	7,8	3,3	5,9
Total capacity (heating mode)	(2)	kW	1,18	1,68	2,28	2,70
Total Net Heating Capacity	(2)(6)	kW	1,19	1,69	2,29	2,72
Water flow in heating mode	(2)	l/s	0,06	0,08	0,11	0,13
Pressure drop in heating mode	(2)	kPa	4,1	9,3	4,2	5,9
Sound Pressure	(3)	dB(A)	30	33	33	34
Sound Power	(4)(7)	dB(A)	40	42	42	43
MED SPEED						
Fan Power Input	(1)	W	13,1	17,1	25,4	40,3
Air flow rate	(1)	m³/h	262	377	548	755
Total capacity in cooling mode	(1)	kW	1,45	2,29	3,01	4,48
Total Net Cooling Capacity	(1)(6)(7)	kW	1,44	2,28	2,99	4,44
Sensible capacity in cooling mode	(1)	kW	1,14	1,74	2,39	3,42
Net sensible cooling capacity	(1)(6)(7)	kW	1,13	1,72	2,36	3,38
Net latent power in cooling	(1)(6)(7)	kW	0,30	0,56	0,63	1,06
Max water flow	(1)	l/s	0,07	0,11	0,14	0,21
Pressure Drop in cooling mode	(1)	kPa	6,7	18,1	8,0	21,4
Total capacity (heating mode)	(2)	kW	1,72	2,58	3,51	5,16
Total Net Heating Capacity	(2)(6)	kW	1,73	2,59	3,53	5,20
Water flow in heating mode	(2)	l/s	0,08	0,12	0,17	0,25
Pressure drop in heating mode	(2)	kPa	8,3	20,6	9,6	19,7
Sound Pressure	(3)	dB(A)	38	42	44	45
Sound Power	(4)(7)	dB(A)	47	51	53	54
MAX SPEED						
Fan Power Input	(1)	W	27,1	39,1	62,9	76,6
Air flow rate	(1)	m³/h	363	586	808	976
Total capacity in cooling mode	(1)	kW	2,00	3,38	4,36	5,68
Total Net Cooling Capacity	(1)(6)(7)	kW	1,97	3,34	4,30	5,60
Sensible capacity in cooling mode	(1)	kW	1,59	2,59	3,49	4,36
Net sensible cooling capacity	(1)(6)(7)	kW	1,56	2,56	3,43	4,28
Net latent power in cooling	(1)(6)(7)	kW	0,41	0,78	0,87	1,32
Max water flow	(1)	l/s	0,10	0,16	0,21	0,27
Pressure Drop in cooling mode	(1)	kPa	12,7	39,3	16,9	34,4
Total capacity (heating mode)	(2)	kW	2,40	3,68	5,09	6,53
Total Net Heating Capacity	(2)(6)	kW	2,43	3,72	5,16	6,60
Water flow in heating mode	(2)	l/s	0,12	0,18	0,25	0,32
Pressure drop in heating mode	(2)	kPa	15,6	40,8	19,6	30,7
Sound Pressure	(3)	dB(A)	48	51	53	54
Sound Power	(4)(7)	dB(A)	57	60	62	63
SIZE AND WEIGHT						
A	(5)	mm	450	650	850	1050
B	(5)	mm	215	215	215	215
H	(5)	mm	450	450	450	450
Operating weight	(5)	kg	11	14	20	24

Notes

- 1 Room temperature 27 °C d.b./19 °C w.b.; Chilled water (in/out) 7/12 °C.
- 2 Room temperature 20 °C d.b.; Hot water (in/out) 45/40 °C
- 3 Sound pressure level in free field on a reflective surface, 1 m from fan front and 1 m from the ground. Non-binding value obtained from sound power level.
- 4 Sound power on the basis of measurements made in compliance with ISO 3741 and Eurovent 8/2.
- 5 Unit in standard configuration/execution, without optional accessories.
- 6 Values in compliance with EN14511
- 7 Values in compliance with [REGULATION (EU) N. 2016/2281]

Certified data in EUROVENT

i-LIFE2 HP DFIO/DLIO		0202	0402	0602	0802	1002	1202
ELECTRICAL DATA							
Power supply	V/ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
2 PIPES SYSTEM CONFIGURATION							
ENERGY EFFICIENCY							
COOLING (EN14511 VALUE)							
FCEER	(1)(6)	kW/kW	125	122	124	120	136
FCEER Class			B	B	B	B	C
HEATING ONLY (EN14511 VALUE)							
FCCOP	(2)(6)	kW/kW	141	162	173	165	183
FCCOP Class			C	B	B	B	C
PERFORMANCE							
MIN SPEED							
Fan Power Input	(1)	W	6,81	11,2	10,9	11,9	17,4
Air flow rate	(1)	m³/h	176	242	289	318	536
Total capacity in cooling mode	(1)	kW	1,00	1,50	1,95	2,35	3,23
Total Net Cooling Capacity	(1)(6)(7)	kW	0,99	1,49	1,94	2,33	3,22
Sensible capacity in cooling mode	(1)	kW	0,79	1,16	1,50	1,83	2,44
Net sensible cooling capacity	(1)(6)(7)	kW	0,78	1,15	1,49	1,82	2,42
Net latent power in cooling	(1)(6)(7)	kW	0,21	0,34	0,45	0,52	0,80
Max water flow	(1)	l/s	0,05	0,07	0,09	0,11	0,15
Pressure Drop in cooling mode	(1)	kPa	3,1	7,8	3,3	5,9	10,1
Total capacity (heating mode)	(2)	kW	1,18	1,68	2,28	2,70	3,61
Total Net Heating Capacity	(2)(6)	kW	1,19	1,69	2,29	2,72	3,63
Water flow in heating mode	(2)	l/s	0,06	0,08	0,11	0,13	0,17
Pressure drop in heating mode	(2)	kPa	4,1	9,3	4,2	5,9	10,8
Sound Pressure	(3)	dB(A)	30	33	33	34	37
Sound Power	(4)(7)	dB(A)	40	42	42	43	46
MED SPEED							
Fan Power Input	(1)	W	13,1	17,1	25,4	40,3	43,1
Air flow rate	(1)	m³/h	262	377	548	755	917
Total capacity in cooling mode	(1)	kW	1,45	2,29	3,01	4,48	5,38
Total Net Cooling Capacity	(1)(6)(7)	kW	1,44	2,28	2,99	4,44	5,34
Sensible capacity in cooling mode	(1)	kW	1,14	1,74	2,39	3,42	4,13
Net sensible cooling capacity	(1)(6)(7)	kW	1,13	1,72	2,36	3,38	4,09
Net latent power in cooling	(1)(6)(7)	kW	0,30	0,56	0,63	1,06	1,26
Max water flow	(1)	l/s	0,07	0,11	0,14	0,21	0,26
Pressure Drop in cooling mode	(1)	kPa	6,7	18,1	8,0	21,4	27,9
Total capacity (heating mode)	(2)	kW	1,72	2,58	3,51	5,16	6,00
Total Net Heating Capacity	(2)(6)	kW	1,73	2,59	3,53	5,20	6,05
Water flow in heating mode	(2)	l/s	0,08	0,12	0,17	0,25	0,29
Pressure drop in heating mode	(2)	kPa	8,3	20,6	9,6	19,7	27,7
Sound Pressure	(3)	dB(A)	38	42	44	45	46
Sound Power	(4)(7)	dB(A)	47	51	53	54	56
MAX SPEED							
Fan Power Input	(1)	W	27,1	39,1	62,9	76,6	105
Air flow rate	(1)	m³/h	363	586	808	976	1351
Total capacity in cooling mode	(1)	kW	2,00	3,38	4,36	5,68	7,50
Total Net Cooling Capacity	(1)(6)(7)	kW	1,97	3,34	4,30	5,60	7,40
Sensible capacity in cooling mode	(1)	kW	1,59	2,59	3,49	4,36	5,81
Net sensible cooling capacity	(1)(6)(7)	kW	1,56	2,56	3,43	4,28	5,71
Net latent power in cooling	(1)(6)(7)	kW	0,41	0,78	0,87	1,32	1,69
Max water flow	(1)	l/s	0,10	0,16	0,21	0,27	0,36
Pressure Drop in cooling mode	(1)	kPa	12,7	39,3	16,9	34,4	53,8
Total capacity (heating mode)	(2)	kW	2,40	3,68	5,09	6,53	8,51
Total Net Heating Capacity	(2)(6)	kW	2,43	3,72	5,16	6,60	8,61
Water flow in heating mode	(2)	l/s	0,12	0,18	0,25	0,32	0,41
Pressure drop in heating mode	(2)	kPa	15,6	40,8	19,6	30,7	52,8
Sound Pressure	(3)	dB(A)	48	51	53	54	56
Sound Power	(4)(7)	dB(A)	57	60	62	63	65
SIZE AND WEIGHT							
A	(5)	mm	545	745	945	1145	1345
B	(5)	mm	215	215	215	215	215
H	(5)	mm	450	450	450	450	450
Operating weight	(5)	kg	12	15	21	25	34

Notes

- 1 Room temperature 27 °C d.b./19 °C w.b.; Chilled water (in/out) 7/12 °C.
 2 Room temperature 20 °C d.b.; Hot water (in/out) 45/40 °C
 3 Sound pressure level in free field on a reflective surface, 1 m from fan front and 1 m from the ground. Non-binding value obtained from sound power level.
 4 Sound power on the basis of measurements made in compliance with ISO 3741 and Eurovent 8/2.

5 Unit in standard configuration/execution, without optional accessories.
 6 Values in compliance with EN14511

7 Values in compliance with [REGULATION (EU) N. 2016/2281]

Certified data in EUROVENT

i-LIFE2 HP DFIV/DLIV	0204	0404	0604	0804	1004	1204
ELECTRICAL DATA						
Power supply	V/ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
4 PIPES SYSTEM CONFIGURATION						
ENERGY EFFICIENCY						
COOLING (EN14511 VALUE)						
FCEER	(1)(6)	kW/kW	125	122	124	120
FCEER Class			B	B	B	C
HEATING ONLY (EN14511 VALUE)						
FCCOP	(2)(6)	kW/kW	104	99	110	103
FCCOP Class			C	D	C	C
PERFORMANCE						
MIN SPEED						
Fan Power Input	(1)	W	6,81	11,2	10,9	11,9
Air flow rate	(1)	m³/h	176	242	289	318
Total capacity in cooling mode	(1)	kW	1,00	1,50	1,95	2,35
Total Net Cooling Capacity	(1)(6)(7)	kW	0,99	1,49	1,94	2,33
Sensible capacity in cooling mode	(1)	kW	0,79	1,16	1,50	1,83
Net sensible cooling capacity	(1)(6)(7)	kW	0,78	1,15	1,49	1,82
Net latent power in cooling	(1)(6)(7)	kW	0,21	0,34	0,45	0,52
Max water flow	(1)	l/s	0,05	0,07	0,09	0,11
Pressure Drop in cooling mode	(1)	kPa	3,1	7,8	3,3	5,9
Total capacity (heating mode)	(2)	kW	0,69	1,01	1,43	1,66
Total Net Heating Capacity	(2)(6)	kW	0,70	1,03	1,45	1,67
Water flow in heating mode	(2)	l/s	0,02	0,02	0,03	0,04
Pressure drop in heating mode	(2)	kPa	2,1	2,8	5,6	2,4
Sound Pressure	(3)	dB(A)	30	33	33	34
Sound Power	(4)(7)	dB(A)	40	42	42	43
MED SPEED						
Fan Power Input	(1)	W	13,1	17,1	25,4	40,3
Air flow rate	(1)	m³/h	262	377	548	755
Total capacity in cooling mode	(1)	kW	1,45	2,29	3,01	4,48
Total Net Cooling Capacity	(1)(6)(7)	kW	1,44	2,28	2,99	4,44
Sensible capacity in cooling mode	(1)	kW	1,14	1,74	2,39	3,42
Net sensible cooling capacity	(1)(6)(7)	kW	1,13	1,72	2,36	3,38
Net latent power in cooling	(1)(6)(7)	kW	0,30	0,56	0,63	1,06
Max water flow	(1)	l/s	0,07	0,11	0,14	0,21
Pressure Drop in cooling mode	(1)	kPa	6,7	18,1	8,0	21,4
Total capacity (heating mode)	(2)	kW	1,00	1,56	2,20	3,16
Total Net Heating Capacity	(2)(6)	kW	1,02	1,57	2,23	3,20
Water flow in heating mode	(2)	l/s	0,02	0,04	0,05	0,08
Pressure drop in heating mode	(2)	kPa	4,1	6,2	12,4	8,1
Sound Pressure	(3)	dB(A)	38	42	44	45
Sound Power	(4)(7)	dB(A)	47	51	53	54
MAX SPEED						
Fan Power Input	(1)	W	27,1	39,1	62,9	76,6
Air flow rate	(1)	m³/h	363	586	808	976
Total capacity in cooling mode	(1)	kW	2,00	3,38	4,36	5,68
Total Net Cooling Capacity	(1)(6)(7)	kW	1,97	3,34	4,30	5,60
Sensible capacity in cooling mode	(1)	kW	1,59	2,59	3,49	4,36
Net sensible cooling capacity	(1)(6)(7)	kW	1,56	2,56	3,43	4,28
Net latent power in cooling	(1)(6)(7)	kW	0,41	0,78	0,87	1,32
Max water flow	(1)	l/s	0,10	0,16	0,21	0,27
Pressure Drop in cooling mode	(1)	kPa	12,7	39,3	16,9	34,4
Total capacity (heating mode)	(2)	kW	1,39	2,28	3,20	4,00
Total Net Heating Capacity	(2)(6)	kW	1,42	2,32	3,26	4,08
Water flow in heating mode	(2)	l/s	0,03	0,06	0,08	0,10
Pressure drop in heating mode	(2)	kPa	7,5	12,9	24,8	12,7
Sound Pressure	(3)	dB(A)	48	51	53	54
Sound Power	(4)(7)	dB(A)	57	60	62	63
SIZE AND WEIGHT						
A	(5)	mm	450	650	850	1050
B	(5)	mm	215	215	215	215
H	(5)	mm	450	450	450	450
Operating weight	(5)	kg	12	15	22	29

Notes

- 1 Room temperature 27°C d.b./18,9°C w.b., Chilled water (in/out) 7°C/12°C.
- 2 Room temperature 20 °C d.b., hot water (in/out) 65/55 °C
- 3 Sound pressure level in free field on a reflective surface, 1 m from fan front and 1 m from the ground. Non-binding value obtained from sound power level.
- 4 Sound power on the basis of measurements made in compliance with ISO 3741 and Eurovent 8/2.

5 Unit in standard configuration/execution, without optional accessories.

6 Values in compliance with EN14511

7 Values in compliance with [REGULATION (EU) N. 2016/2281]

Certified data in EUROVENT

i-LIFE2 HP DFIO/DLIO		0204	0404	0604	0804	1004	1204
ELECTRICAL DATA							
Power supply	V/ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
4 PIPES SYSTEM CONFIGURATION							
ENERGY EFFICIENCY							
COOLING (EN14511 VALUE)							
FCEER	(1)(6)	kW/kW	125	122	124	120	136
FCEER Class			B	B	B	B	C
HEATING ONLY (EN14511 VALUE)							
FCCOP	(2)(6)	kW/kW	104	99	110	103	116
FCCOP Class			C	D	C	C	D
PERFORMANCE							
MIN SPEED							
Fan Power Input	(1)	W	6,81	11,2	10,9	11,9	17,4
Air flow rate	(1)	m³/h	176	242	289	318	536
Total capacity in cooling mode	(1)	kW	1,00	1,50	1,95	2,35	3,23
Total Net Cooling Capacity	(1)(6)(7)	kW	0,99	1,49	1,94	2,33	3,22
Sensible capacity in cooling mode	(1)	kW	0,79	1,16	1,50	1,83	2,44
Net sensible cooling capacity	(1)(6)(7)	kW	0,78	1,15	1,49	1,82	2,42
Net latent power in cooling	(1)(6)(7)	kW	0,21	0,34	0,45	0,52	0,80
Max water flow	(1)	l/s	0,05	0,07	0,09	0,11	0,15
Pressure Drop in cooling mode	(1)	kPa	3,1	7,8	3,3	5,9	10,1
Total capacity (heating mode)	(2)	kW	0,69	1,01	1,43	1,66	2,27
Total Net Heating Capacity	(2)(6)	kW	0,70	1,03	1,45	1,67	2,28
Water flow in heating mode	(2)	l/s	0,02	0,02	0,03	0,04	0,06
Pressure drop in heating mode	(2)	kPa	2,1	2,8	5,6	2,4	3,5
Sound Pressure	(3)	dB(A)	30	33	33	34	37
Sound Power	(4)(7)	dB(A)	40	42	42	43	46
MED SPEED							
Fan Power Input	(1)	W	13,1	17,1	25,4	40,3	43,1
Air flow rate	(1)	m³/h	262	377	548	755	917
Total capacity in cooling mode	(1)	kW	1,45	2,29	3,01	4,48	5,38
Total Net Cooling Capacity	(1)(6)(7)	kW	1,44	2,28	2,99	4,44	5,34
Sensible capacity in cooling mode	(1)	kW	1,14	1,74	2,39	3,42	4,13
Net sensible cooling capacity	(1)(6)(7)	kW	1,13	1,72	2,36	3,38	4,09
Net latent power in cooling	(1)(6)(7)	kW	0,30	0,56	0,63	1,06	1,26
Max water flow	(1)	l/s	0,07	0,11	0,14	0,21	0,26
Pressure Drop in cooling mode	(1)	kPa	6,7	18,1	8,0	21,4	27,9
Total capacity (heating mode)	(2)	kW	1,00	1,56	2,20	3,16	3,78
Total Net Heating Capacity	(2)(6)	kW	1,02	1,57	2,23	3,20	3,82
Water flow in heating mode	(2)	l/s	0,02	0,04	0,05	0,08	0,09
Pressure drop in heating mode	(2)	kPa	4,1	6,2	12,4	8,1	9,2
Sound Pressure	(3)	dB(A)	38	42	44	45	46
Sound Power	(4)(7)	dB(A)	47	51	53	54	56
MAX SPEED							
Fan Power Input	(1)	W	27,1	39,1	62,9	76,6	105
Air flow rate	(1)	m³/h	363	586	808	976	1351
Total capacity in cooling mode	(1)	kW	2,00	3,38	4,36	5,68	7,50
Total Net Cooling Capacity	(1)(6)(7)	kW	1,97	3,34	4,30	5,60	7,40
Sensible capacity in cooling mode	(1)	kW	1,59	2,59	3,49	4,36	5,81
Net sensible cooling capacity	(1)(6)(7)	kW	1,56	2,56	3,43	4,28	5,71
Net latent power in cooling	(1)(6)(7)	kW	0,41	0,78	0,87	1,32	1,69
Max water flow	(1)	l/s	0,10	0,16	0,21	0,27	0,36
Pressure Drop in cooling mode	(1)	kPa	12,7	39,3	16,9	34,4	53,8
Total capacity (heating mode)	(2)	kW	1,39	2,28	3,20	4,00	5,27
Total Net Heating Capacity	(2)(6)	kW	1,42	2,32	3,26	4,08	5,37
Water flow in heating mode	(2)	l/s	0,03	0,06	0,08	0,10	0,13
Pressure drop in heating mode	(2)	kPa	7,5	12,9	24,8	12,7	17,2
Sound Pressure	(3)	dB(A)	48	51	53	54	56
Sound Power	(4)(7)	dB(A)	57	60	62	63	65
SIZE AND WEIGHT							
A	(5)	mm	545	745	945	1145	1345
B	(5)	mm	215	215	215	215	215
H	(5)	mm	450	450	450	450	450
Operating weight	(5)	kg	12	16	22	26	30

Notes

- 1 Room temperature 27°C d.b./18,9°C w.b., Chilled water (in/out) 7°C/12°C.
 2 Room temperature 20 °C d.b., hot water (in/out) 65/55 °C
 3 Sound pressure level in free field on a reflective surface, 1 m from fan front and 1 m from the ground. Non-binding value obtained from sound power level.
 4 Sound power on the basis of measurements made in compliance with ISO 3741 and Eurovent 8/2.

5 Unit in standard configuration/execution, without optional accessories.

6 Values in compliance with EN14511

7 Values in compliance with [REGULATION (EU) N. 2016/2281]

Certified data in EUROVENT

Dimensional drawing

