



Outdoor unit for the production of chilled water with fixed speed and variable speed (Inverter Driven) Scroll compressors, optimized for R410A in a single-circuit configuration, axial-flow fans, micro-channel full-aluminum air coils and electronic expansion valve as standard equipment.

Flexible and reliable unit; it easily adapts itself to different thermal load conditions thanks to the precise temperature control together with the use of inverter technology. The high performance's level, both full and partial load, is achieved thanks to the accurate unit's design and to the use of fixed speed motor together with variable speed (inverter) motor.

Control



Electronic control W3000TE

The brand new W3000TE controller offers advanced functions and algorithms. The keypad W3000 Compact, as standard equipment, features function controls and a complete LCD display for viewing data and activating the unit, via a multilevel menu, with settable display language. In addition to or as an alternative, the KIPLink is available - Keyboard In Your Pocket - is the innovative user interface based on WiFi technology that allows one to operate on the unit directly from the smartphone or tablet. Using KIPLink, it is possible to turn the unit on and off, adjust the set-point, plot the main operating variables, monitor in detail the status of the refrigerant circuits, the compressors, the fans and the pumps (if present) and display and reset the possible alarms. The regulation features the continuous modulation of capacity, based on sequential adjustment + DIP referring to the leaving water temperature (neutral zone adjustment + DIP on outlet temperature probe, for the 0151 size). Diagnostics include complete alarm management, with "blackbox" functions (via PC) and alarm log (display or PC) for best analysis of unit behaviour. The built-in clock can be used to create an operating profile containing up to 4 typical days and 10 time bands, essential for efficient programming of energy production. Optional proprietary devices can perform the adjustment of the resources in systems made of several units. Consumption metering and performance measurement are possible as well. Supervision is available with different options, using proprietary devices or by integration into third party systems using ModBus, BACnet, BACnet-over-IP and Echelon LonWorks protocols. A dedicated wall-mounted keypad can be used for remote control of all the functions. Optionally (VPF package), capacity modulation can be integrated with hydraulic flow modulation, thanks to inverter-driven pumps and to specific resources for the hydraulic circuit.

Refrigerant



Versions

- Basic SL Super-low noise version

Configurations

- Basic function D Partial condensing heat recovery function

Features

HIGH EFFICIENCY

Unit with high efficiency and reduced energy consumption, thanks to the inverter technology, contributing to lower operating costs and therefore achieving a quick return on investment.

ErP READY

Thanks to the inverter technology, the high level of efficiency at part load meets and exceeds the minimum seasonal efficiency required by the Ecodesign Directive starting from 2021.

VARIBLE PRIMARY FLOW (OPTION)

Energy saving due to variable pump speed management based on load demand and the variable flow assures the functioning of the units also with critical working conditions.

INTEGRATED HYDRONIC MODULE

The built-in hydronic module already contains the main water circuit components; it is available as option with single or twin in-line pump, for achieving low or high head, fixed or variable speed and buffer tank.

ALUMINIUM MICRO-CHANNEL HEAT EXCHANGERS

This new range of chiller uses aluminum micro-channel condensers that ensure a premium level of efficiency. This solution also allows to reduce the refrigerant charge with respect to traditional copper/aluminium coils and to reduce the weight of the unit.

WIDE OPERATING RANGE

Full load operation is ensured with outdoor air temperature up to 48°C during summer. Dedicated accessories allow the unit operation down to -20°C of outdoor air temperature during winter. Production of evaporator leaving water temperature from -10°C to 20°C.

Accessories

- Remote control keyboard (distance to 200m and to 500m)
- Set-up for remote connectivity with ModBus/Echelon protocol cards
- Compressor power factor correction
- Soft start
- Hydronic kit available in different configurations with 1 or 2 pumps fixed speed or variable speed and buffer tank
- VPF (Variable Primary Flow) system
- EC fans with electronic DC brushless motor
- LOW NOISE KIT (only on no silenced versions)
- User Limit Control (U.L.C.) allows the safe startup of the unit in critical conditions of water and air temperature.
- Night mode is a system setting to limit maximum noise level of the unit.
- Microchannel coils with e-coating protection
- Traditional coils with copper tubes and aluminium fins, also available with pre-painted fins or Fin Guard Silver protective treatment.

i-NX			0151P	0182P	0202P	0262P	0302P	0352P	0402P	0502P
Power supply		V/ph/Hz	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3/50	400/3/50	400/3/50
PERFORMANCE										
COOLING ONLY (GROSS VALUE)										
Cooling capacity	(1)	kW	43,88	52,86	63,14	72,07	83,83	100,9	119,7	129,3
Total power input	(1)	kW	15,72	18,79	21,36	24,95	29,15	35,20	41,92	46,84
EER	(1)	kW/kW	2,796	2,814	2,949	2,884	2,870	2,866	2,857	2,763
ESEER	(1)	kW/kW	4,560	4,550	4,510	4,540	4,510	4,660	4,580	4,530
COOLING ONLY (EN14511 VALUE)										
Cooling capacity	(1)(2)	kW	43,60	52,60	62,70	71,70	83,40	100,4	119,1	128,7
EER	(1)(2)	kW/kW	2,730	2,750	2,880	2,820	2,820	2,810	2,800	2,720
ESEER	(1)(2)	kW/kW	4,270	4,190	4,170	4,230	4,240	4,360	4,270	4,250
Cooling energy class			C	C	C	C	C	C	C	C
ENERGY EFFICIENCY										
SEASONAL EFFICIENCY IN COOLING (Reg. EU 2016/2281)										
Ambient refrigeration										
Prated,c	(7)	kW	43,6	52,6	62,7	71,7	83,4	100	119	129
SEER	(7)(8)		4,15	4,11	4,13	4,18	4,23	4,36	4,32	4,30
Performance ηs	(7)(9)	%	163	161	162	164	166	171	170	169
EXCHANGERS										
HEAT EXCHANGER USER SIDE IN REFRIGERATION										
Water flow	(1)	l/s	2,098	2,528	3,020	3,446	4,009	4,824	5,726	6,181
Pressure drop	(1)	kPa	37,2	41,2	42,3	39,4	35,0	36,2	42,9	38,9
REFRIGERANT CIRCUIT										
Compressors nr.		N°	1	2	2	2	2	2	2	2
No. Circuits		N°	1	1	1	1	1	1	1	1
Refrigerant charge		kg	7,00	7,20	8,90	9,40	9,50	12,5	12,9	13,5
NOISE LEVEL										
Sound Pressure	(3)	dB(A)	51	52	53	53	54	55	57	57
Sound power level in cooling	(4)(5)	dB(A)	83	84	85	85	86	87	89	89
SIZE AND WEIGHT										
A	(6)	mm	2000	2000	2625	2625	2625	3250	3250	3250
B	(6)	mm	1350	1350	1350	1350	1350	1350	1350	1350
H	(6)	mm	2070	2070	2070	2070	2070	2170	2170	2170
Operating weight	(6)	kg	600	660	750	780	810	1060	1070	1080

Notes

- Plant (side) cooling exchanger water (in/out) 12°C/7°C; Source (side) heat exchanger air (in) 35°C.
- Values in compliance with EN14511
- Average sound pressure level at 10m distance, unit in a free field on a reflective surface; non-binding value calculated from the sound power level.
- Sound power on the basis of measurements made in compliance with ISO 9614.
- Sound power level in cooling, outdoors.
- Unit in standard configuration/execution, without optional accessories.
- Parameter calculated according to [REGULATION (EU) N. 2016/2281]
- Seasonal energy efficiency ratio
- Seasonal space cooling energy efficiency

The units highlighted in this publication contain HFC R410A [GWP₁₀₀ 2088] fluorinated greenhouse gases.
Certified data in EUROVENT

i-NX / SL			0151P	0182P	0202P	0262P	0302P	0352P	0402P	0502P
Power supply		V/ph/Hz	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3/50	400/3/50	400/3/50	400/3/50
PERFORMANCE										
COOLING ONLY (GROSS VALUE)										
Cooling capacity	(1)	kW	42,60	51,20	60,09	68,07	81,23	96,66	115,1	124,3
Total power input	(1)	kW	14,40	17,78	20,91	24,45	28,26	33,95	39,27	44,30
EER	(1)	kW/kW	2,958	2,876	2,876	2,780	2,869	2,853	2,929	2,806
ESEER	(1)	kW/kW	4,480	4,580	4,490	4,550	4,540	4,750	4,780	4,700
COOLING ONLY (EN14511 VALUE)										
Cooling capacity	(1)(2)	kW	42,30	50,90	59,80	67,70	80,80	96,30	114,6	123,8
EER	(1)(2)	kW/kW	2,890	2,810	2,820	2,730	2,820	2,810	2,880	2,760
ESEER	(1)(2)	kW/kW	4,210	4,260	4,200	4,250	4,260	4,480	4,500	4,430
Cooling energy class			C	C	C	C	C	C	C	C
ENERGY EFFICIENCY										
SEASONAL EFFICIENCY IN COOLING (Reg. EU 2016/2281)										
Ambient refrigeration										
Prated,c	(7)	kW	42,3	50,9	59,8	67,7	80,8	96,3	115	124
SEER	(7)(8)		4,18	4,10	4,11	4,17	4,22	4,46	4,50	4,48
Performance ηs	(7)(9)	%	164	161	162	164	166	176	177	176
EXCHANGERS										
HEAT EXCHANGER USER SIDE IN REFRIGERATION										
Water flow	(1)	l/s	2,037	2,449	2,874	3,255	3,885	4,622	5,504	5,946
Pressure drop	(1)	kPa	35,1	38,7	38,3	35,2	32,9	33,2	39,6	36,0
REFRIGERANT CIRCUIT										
Compressors nr.		N°	1	2	2	2	2	2	2	2
No. Circuits		N°	1	1	1	1	1	1	1	1
Refrigerant charge		kg	8,10	8,30	8,70	9,20	11,8	12,3	14,7	15,2
NOISE LEVEL										
Sound Pressure	(3)	dB(A)	45	45	46	46	47	48	50	50
Sound power level in cooling	(4)(5)	dB(A)	77	77	78	78	79	80	82	82
SIZE AND WEIGHT										
A	(6)	mm	2625	2625	2625	2625	3250	3250	3875	3875
B	(6)	mm	1350	1350	1350	1350	1350	1350	1350	1350
H	(6)	mm	2070	2070	2070	2070	2170	2170	2170	2170
Operating weight	(6)	kg	700	760	790	820	980	1090	1180	1200

Notes

- 1 Plant (side) cooling exchanger water (in/out) 12°C/7°C; Source (side) heat exchanger air (in) 35°C.
- 2 Values in compliance with EN14511
- 3 Average sound pressure level at 10m distance, unit in a free field on a reflective surface; non-binding value calculated from the sound power level.
- 4 Sound power on the basis of measurements made in compliance with ISO 9614.
- 5 Sound power level in cooling, outdoors.
- 6 Unit in standard configuration/execution, without optional accessories.
- 7 Parameter calculated according to [REGULATION (EU) N. 2016/2281]
- 8 Seasonal energy efficiency ratio
- 9 Seasonal space cooling energy efficiency

The units highlighted in this publication contain HFC R410A [GWP₁₀₀ 2088] fluorinated greenhouse gases.
Certified data in EUROVENT

Dimensional drawing

