

# MSZ-A SERIES

Indoor Unit

R32 R410A



MSZ-AP15/20VF



Outdoor Unit

For MXZ Connection Only

Remote Controller



Type		Inverter Heat Pump													
Indoor Unit		MSZ-AP15VF		MSZ-AP20VF		MSZ-AP25VG(K)		MSZ-AP25VG(K)		MSZ-AP35VG(K)		MSZ-AP35VG(K)			
Outdoor Unit		for MXZ connection						MUZ-AP25VG		MUZ-AP25VGH		MUZ-AP35VG		MUZ-AP35VGH	
Refrigerant		Single: R32 <sup>(1)</sup> / Multi: R410A or R32 <sup>(1)</sup>													
Power Source		Outdoor Power supply													
Supply		Outdoor (V / Phase / Hz)						230/Single/50							
Cooling	Design load	kW		-		2.5		2.5		3.5		3.5			
	Annual electricity consumption <sup>(2)</sup>	kWh/a		-		101		101		142		142			
	SEER <sup>(4)</sup>	-		-		8.6		8.6		8.6		8.6			
	Capacity	Energy efficiency class		-		A+++		A+++		A+++		A+++			
		Rated	kW		-		2.5		2.5		3.5		3.5		
Heating (Average Season) <sup>(5)</sup>	Declared Capacity	at reference design temperature		-		2.4 (-10°C)		2.4 (-10°C)		2.9 (-10°C)		2.9 (-10°C)			
		at bivalent temperature		-		2.4 (-10°C)		2.4 (-10°C)		2.9 (-10°C)		2.9 (-10°C)			
	at operation limit temperature		-		2.4 (-15°C)		2.2 (-20°C)		2.6 (-15°C)		2.4 (-20°C)		2.4 (-20°C)		
	Back up heating capacity	kW		-		0.0 (-10°C)		0.0 (-10°C)		0.0 (-10°C)		0.0 (-10°C)			
	Annual electricity consumption <sup>(2)</sup>	kWh/a		-		698		703		862		873			
Capacity	Energy efficiency class		-		A++		A++		A++		A++				
	Rated	kW		-		3.2		3.2		4.0		4.0			
Total Input	Min-Max		-		-		1.0-4.1		1.0-4.1		1.3-4.6		1.3-4.6		
	Rated	kW		-		0.780		0.780		1.030		1.030			
Operating Current (Max)		A		-		7.1		7.1		8.5		8.5			
Indoor Unit	Input	Rated	kW		0.017		0.019		0.026		0.026		0.026		
		Operating Current(Max)	A		0.17		0.19		0.3		0.3		0.3		
	Dimensions	H*W*D		mm		250-760-178		250-760-178		299-798-219		299-798-219			
	Weight	kg		8.2		8.2		10.5		10.5		10.5			
	Air Volume (SLo-Lo-Mid-Hi-SH <sup>(3)</sup> Dry/Wet)	Cooling	m <sup>3</sup> /min		3.5 - 3.9 - 4.6 - 5.5 - 6.4		3.5 - 3.9 - 4.6 - 5.5 - 6.9		4.9 - 5.9 - 7.1 - 8.7 - 11.4		4.9 - 5.9 - 7.1 - 8.7 - 11.4		4.9 - 5.9 - 7.1 - 8.7 - 11.4		
		Heating	m <sup>3</sup> /min		3.7 - 4.4 - 5.0 - 6.0 - 6.8		3.7 - 4.4 - 5.0 - 6.0 - 7.3		4.9 - 5.9 - 7.3 - 8.9 - 12.9		4.9 - 5.9 - 7.3 - 8.9 - 12.9		4.9 - 5.9 - 7.3 - 8.9 - 12.9		
	Sound Level (SPL) (SLo-Lo-Mid-Hi-SH <sup>(3)</sup> )	Cooling	dB(A)		21 - 26 - 30 - 35 - 40		21 - 26 - 30 - 35 - 42		19 - 24 - 30 - 36 - 42		19 - 24 - 30 - 36 - 42		19 - 24 - 30 - 36 - 42		
		Heating	dB(A)		21 - 26 - 30 - 35 - 40		21 - 26 - 30 - 35 - 42		19 - 24 - 34 - 39 - 45		19 - 24 - 34 - 39 - 45		19 - 24 - 31 - 38 - 45		
	Sound Level (PWL)	Cooling	dB(A)		59		60		57		57		57		
		Heating	dB(A)		-		-		48		48		50		
Dimensions	H*W*D		mm		-		550-800-285		550-800-285		550-800-285		550-800-285		
Weight	kg		-		-		31		31		31		31		
Outdoor Unit	Air Volume	Cooling	m <sup>3</sup> /min		-		32.2		32.2		33.8		33.8		
		Heating	m <sup>3</sup> /min		-		29.8		29.8		33.8		33.8		
	Sound Level (SPL)	Cooling	dB(A)		-		47		47		49		49		
		Heating	dB(A)		-		48		48		50		50		
	Sound Level (PWL)	Cooling	dB(A)		-		59		59		61		61		
Heating		dB(A)		-		-		6.8		8.2		8.2			
Operating Current (Max)		A		-		-		6.8		8.2		8.2			
Breaker Size		A		-		-		10		10		10			
Ext. Piping	Diameter	Liquid/Gas		mm		6.35/9.52		6.35/9.52		6.35/9.52		6.35/9.52			
	Max.Length	Out-In		m		-		20		20		20			
	Max.Height	Out-In		m		-		12		12		12			
Guaranteed Operating Range (Outdoor)	Cooling	°C		-		-		-10 ~ +46		-10 ~ +46		-10 ~ +46			
	Heating	°C		-		-		-15 ~ +24		-20 ~ +24		-15 ~ +24			

(1) Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 550. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 550 times higher than 1 kg of CO<sub>2</sub> over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.  
The GWP of R32 is 675 in the IPCC 4th Assessment Report.

(2) Energy consumption based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

(3) SH: Super High

(4) SEER, SCOP and other related description are based on COMMISSION DELEGATED REGULATION (EU) No.626/2011. The temperature conditions for calculating SCOP are based on "Average Season".

(5) Please see page 63 for heating (warmer season) specifications.