



Indoor unit for the production of chilled water featuring semihermetic screw compressors optimized to operate with low compression ratio and R513A, electronic expansion valve, shell and tube condenser and shell and tube flooded evaporator.

The unit results extremely compact, thanks to the peculiar construction layout, without base, frame and panels. At the same time high efficiency is guaranteed by the innovative optimized compressors and high performing heat exchangers, enhancing the EER values up to 5,8 at Eurovent standard conditions.

Control



W3000TE

W3000TE features a large keyboard and wide LCD display for an easy and safe access to the machine setup and a complete view of unit's status. The assessment and intervention on the unit is managed through a multi-level menu, with selectable user's language. An optional extra is the touch screen interface: 7.0" WVGA colour display with adjustable LED backlight and front USB port. The touch screen technology allows intuitive navigation between the various screens, safe access to the data with a three-level password protection as well as the graphic display of the performance of some monitored measurements. Complete alarm management system is available, with the "black-box" and the alarm history display functions. For the systems made of several units, the adjustment of the resources is performed by optional proprietary devices. Consumption metering and performance measurement are possible and supervision can be developed via proprietary devices or the integration in third party systems by means of the most common protocols ModBus, Bacnet, Bacnet-over-IP, LonWorks.

Compatibility with remote keyboard (up to 8 units). The programmable timer allows the creation of an operating profile up to 4 typical days and 10 time bands. Continuous modulation of the unit capacity, based on PID algorithms and referring to the water delivery temperature.

Refrigerant



Versions

CA High energy efficiency units

Features

HIGH EFFICIENCY

Very high efficiency at full and partial load, at the highest market levels, thanks to the adopted technological solutions. These units ensure low operating costs and therefore a quick payback time.

ADAPTABILITY

Adaptability at the building's cooling request thanks to the continuous capacity regulation, assured by sophisticated control's logic.

MAXIMUM COMPACTNESS

Maximum compactness to achieve a very high flexibility in the design process and installation operations, offering a premium solution in case of reduced clearances or when retrofitting existing installations.

AHRI CERTIFICATION

Certified in accordance with the AHRI Water-Cooled Water-Chilling and Heat Pump Water-Heating Packages Certification Program, which is based on AHRI Standard 550/590 (I-P). Certified units may be found in the AHRI Directory at www.ahridirectory.org

Accessories

- Touch Screen visual display
- VPF (Variable Primary Flow) system
- Set-up for remote connectivity with ModBus/Echelon protocol cards
- Several devices for condensation's control

FOCS3-W-G05			0551	0701	0851	0951	1101	1301	1401
Power supply		V/ph/Hz	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50
PERFORMANCE									
COOLING ONLY (GROSS VALUE)									
Cooling capacity	(1)	kW	188,2	250,0	306,0	337,6	383,5	459,9	524,0
Total power input	(1)	kW	36,40	47,78	58,45	63,77	72,73	85,99	96,90
EER	(1)	kW/kW	5,170	5,230	5,231	5,292	5,275	5,348	5,408
ESEER	(1)	kW/kW	6,910	7,150	6,560	6,830	6,800	6,730	7,250
COOLING ONLY (EN14511 VALUE)									
Cooling capacity	(1)(2)	kW	187,4	248,9	304,7	336,1	381,9	458,2	522,3
EER	(1)(2)	kW/kW	4,890	4,950	4,960	5,010	5,000	5,090	5,190
ESEER	(1)(2)	kW/kW	6,180	6,370	5,950	6,150	6,140	6,140	6,670
Cooling energy class			B	B	B	B	B	A	A
ENERGY EFFICIENCY									
SEASONAL EFFICIENCY IN COOLING (Reg. EU 2016/2281)									
Ambient refrigeration									
Prated,c	(7)	kW	187	249	305	336	382	458	522
SEER	(7)(8)		5,81	6,04	5,62	5,78	5,79	5,94	6,50
Performance ηs	(7)(9)	%	224	234	217	223	223	230	252
EXCHANGERS									
HEAT EXCHANGER USER SIDE IN REFRIGERATION									
Water flow	(1)	l/s	9,001	11,95	14,63	16,15	18,34	21,99	25,06
Pressure drop	(1)	kPa	42,0	48,7	49,1	52,4	52,8	47,5	39,9
HEAT EXCHANGER SOURCE SIDE IN REFRIGERATION									
Water flow	(1)	l/s	10,70	14,19	17,36	19,13	21,74	26,02	29,60
Pressure drop	(1)	kPa	57,4	57,9	56,7	59,3	58,1	55,2	44,8
REFRIGERANT CIRCUIT									
Compressors nr.		N°	1	1	1	1	1	1	1
No. Circuits		N°	1	1	1	1	1	1	1
Refrigerant charge		kg	83,0	95,0	105	104	95,0	110	121
NOISE LEVEL									
Sound Pressure	(3)	dB(A)	77	77	80	80	80	80	80
Sound power level in cooling	(4)(5)	dB(A)	95	95	98	98	98	98	98
SIZE AND WEIGHT									
A	(6)	mm	2920	2920	2920	2920	2920	2900	2900
B	(6)	mm	1180	1180	1180	1180	1180	1180	1180
H	(6)	mm	1870	1870	1870	1870	1870	1960	1970
Operating weight	(6)	kg	1740	1790	2170	2200	2260	2940	3020

Notes

- 1 Plant (side) cooling exchanger water (in/out) 12°C/7°C; Source (side) heat exchanger water (in/out) 30°C/35°C.
- 2 Values in compliance with EN14511
- 3 Average sound pressure level at 1m distance, unit in a free field on a reflective surface; non-binding value calculated from the sound power level.
- 4 Sound power on the basis of measurements made in compliance with ISO 9614.
- 5 Sound power level in cooling, indoors.
- 6 Unit in standard configuration/execution, without optional accessories.
- 7 Parameter calculated according to [REGULATION (EU) N. 2016/2281]
- 8 Seasonal energy efficiency ratio
- 9 Seasonal space cooling energy efficiency

The units highlighted in this publication contain R513A [GWP₁₀₀ 631] fluorinated greenhouse gases.
 Certified data in EUROVENT

FOCS3-W-G05		1651	1901	2101	2501	2602	3002	3152
Power supply	V/ph/Hz	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50
PERFORMANCE								
COOLING ONLY (GROSS VALUE)								
Cooling capacity	(1) kW	591,8	681,6	741,3	837,0	915,9	1062	1140
Total power input	(1) kW	108,2	127,0	138,7	155,6	171,0	194,8	204,3
EER	(1) kW/kW	5,470	5,367	5,345	5,379	5,356	5,452	5,580
ESEER	(1) kW/kW	6,960	7,020	6,920	6,800	7,060	7,330	7,530
COOLING ONLY (EN14511 VALUE)								
Cooling capacity	(1)(2) kW	589,5	679,4	738,9	834,3	913,2	1058	1137
EER	(1)(2) kW/kW	5,200	5,120	5,130	5,160	5,160	5,210	5,400
ESEER	(1)(2) kW/kW	6,310	6,390	6,400	6,280	6,400	6,480	6,870
Cooling energy class		A	A	A	A	A	A	A
ENERGY EFFICIENCY								
SEASONAL EFFICIENCY IN COOLING (Reg. EU 2016/2281)								
Ambient refrigeration								
Prated,c	(7) kW	590	679	739	834	913	1058	1137
SEER	(7)(8)	6,12	6,19	6,27	6,19	6,28	6,37	6,89
Performance ηs	(7)(9) %	237	240	243	240	243	247	267
EXCHANGERS								
HEAT EXCHANGER USER SIDE IN REFRIGERATION								
Water flow	(1) l/s	28,30	32,59	35,45	40,03	43,80	50,79	54,53
Pressure drop	(1) kPa	50,9	42,0	42,7	42,8	40,0	51,5	37,4
HEAT EXCHANGER SOURCE SIDE IN REFRIGERATION								
Water flow	(1) l/s	33,37	38,54	41,94	47,31	51,80	59,91	64,10
Pressure drop	(1) kPa	55,8	60,4	45,8	48,1	44,5	54,4	32,0
REFRIGERANT CIRCUIT								
Compressors nr.	N°	1	1	1	1	2	2	2
No. Circuits	N°	1	1	1	1	2	2	2
Refrigerant charge	kg	124	134	162	201	231	274	297
NOISE LEVEL								
Sound Pressure	(3) dB(A)	80	80	82	82	81	81	81
Sound power level in cooling	(4)(5) dB(A)	98	98	100	100	100	100	100
SIZE AND WEIGHT								
A	(6) mm	2900	2930	2980	2990	4430	4430	4440
B	(6) mm	1180	1180	1190	1280	1270	1270	1270
H	(6) mm	1960	2050	2100	2200	2210	2210	2280
Operating weight	(6) kg	3150	3270	3570	3960	6200	6430	7080

Notes

- Plant (side) cooling exchanger water (in/out) 12°C/7°C; Source (side) heat exchanger water (in/out) 30°C/35°C.
- Values in compliance with EN14511
- Average sound pressure level at 1m distance, unit in a free field on a reflective surface; non-binding value calculated from the sound power level.
- Sound power on the basis of measurements made in compliance with ISO 9614.
- Sound power level in cooling, indoors.
- Unit in standard configuration/execution, without optional accessories.
- Parameter calculated according to [REGULATION (EU) N. 2016/2281]
- Seasonal energy efficiency ratio
- Seasonal space cooling energy efficiency

The units highlighted in this publication contain R513A [GWP₁₀₀ 631] fluorinated greenhouse gases.

Certified data in EUROVENT

FOCS3-W-G05			3502	3652	4002	4102	4502	4602	4752
Power supply		V/ph/Hz	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50
PERFORMANCE									
COOLING ONLY (GROSS VALUE)									
Cooling capacity	(1)	kW	1218	1303	1382	1450	1522	1614	1693
Total power input	(1)	kW	222,9	234,1	251,9	263,1	279,3	295,9	304,3
EER	(1)	kW/kW	5,464	5,566	5,486	5,511	5,449	5,455	5,564
ESEER	(1)	kW/kW	7,150	7,400	7,130	7,200	7,190	7,230	7,500
COOLING ONLY (EN14511 VALUE)									
Cooling capacity	(1)(2)	kW	1214	1299	1377	1445	1517	1609	1688
EER	(1)(2)	kW/kW	5,220	5,380	5,250	5,290	5,210	5,240	5,320
ESEER	(1)(2)	kW/kW	6,330	6,740	6,350	6,450	6,410	6,500	6,660
Cooling energy class			A	A	A	A	A	A	A
ENERGY EFFICIENCY									
SEASONAL EFFICIENCY IN COOLING (Reg. EU 2016/2281)									
Ambient refrigeration									
Prated,c	(7)	kW	1214	1299	1377	1445	1517	1609	1688
SEER	(7)(8)		6,24	6,76	6,30	6,50	6,34	6,41	6,62
Performance ηs	(7)(9)	%	242	262	244	252	246	248	257
EXCHANGERS									
HEAT EXCHANGER USER SIDE IN REFRIGERATION									
Water flow	(1)	l/s	58,23	62,33	66,11	69,33	72,76	77,20	80,94
Pressure drop	(1)	kPa	51,4	39,8	50,4	46,7	51,5	42,5	46,7
HEAT EXCHANGER SOURCE SIDE IN REFRIGERATION									
Water flow	(1)	l/s	68,67	73,30	77,91	81,66	85,84	91,05	95,19
Pressure drop	(1)	kPa	56,8	34,1	53,5	50,1	55,4	53,7	58,7
REFRIGERANT CIRCUIT									
Compressors nr.		N°	2	2	2	2	2	2	2
No. Circuits		N°	2	2	2	2	2	2	2
Refrigerant charge		kg	297	308	308	317	327	376	376
NOISE LEVEL									
Sound Pressure	(3)	dB(A)	81	81	81	82	82	82	82
Sound power level in cooling	(4)(5)	dB(A)	100	100	100	101	102	102	102
SIZE AND WEIGHT									
A	(6)	mm	4470	4470	4470	4565	4650	5270	5270
B	(6)	mm	1270	1320	1270	1320	1320	1320	1320
H	(6)	mm	2250	2330	2280	2380	2380	2380	2380
Operating weight	(6)	kg	7160	7560	7280	7850	7940	8420	8950

- Notes**
- Plant (side) cooling exchanger water (in/out) 12°C/7°C; Source (side) heat exchanger water (in/out) 30°C/35°C.
 - Values in compliance with EN14511
 - Average sound pressure level at 1m distance, unit in a free field on a reflective surface; non-binding value calculated from the sound power level.
 - Sound power on the basis of measurements made in compliance with ISO 9614.
 - Sound power level in cooling, indoors.
 - Unit in standard configuration/execution, without optional accessories.
 - Parameter calculated according to [REGULATION (EU) N. 2016/2281]
 - Seasonal energy efficiency ratio
 - Seasonal space cooling energy efficiency
- The units highlighted in this publication contain R513A [GWP₁₀₀ 631] fluorinated greenhouse gases.
 Certified data in EUROVENT

Dimensional drawing

